Theory of sound propagation in superfluid-filled porous media

T.Buishvili Dept. of Physics, Tbilisi State University, Chavchavadze ave. 3, Tbilisi 380028, Georgia,

Sh.Kekutia, O.Tkeshelashvili Institute of Cybernetics, Sandro Euli str. 5, Tbilisi 380086, Georgia,

L.Tkeshelashvili

Institut für Theorie der Kondensierten Materie, University of Karlsruhe, P.O. Box 6980, 76128 Karlsruhe, Germany; Institute of Physics, Tamarashvili str. 6, Tbilisi 380077, Georgia, E-mail: lasha@tkm.physik.uni-karlsruhe.de

Abstract

The theory of sound propagation in macroscopically isotropic and homogeneous porous media saturated with superfluid ⁴He has been developed neglecting all damping processes. The case when the normal fluid component is locked inside a porous medium by viscous forces is investigated in detail. It is shown that in this case one shear wave and two longitudinal, fast and slow, waves exist. Fast wave as well as slow wave is accompanied with temperature oscillations. The velocities of these waves are obtained.

PACS numbers: 81.05.Rm; 47.35.+i; 82.33.Ln; 47.37.+q; KEY words: porous materials; hydrodynamical waves;

1 Introduction

The investigation of acoustic propagation in a fluid-saturated porous media provides opportunities to study disordered pore structures, as well as the properties of the fluids confined in the pores. In [1] Biot developed a simple theory of propagation of elastic waves in statistically homogeneous and isotropic porous media saturated with a (one-component) compressional fluid assuming that pore sizes are smaller compared to the wavelength i.e. the long wavelength limit is considered. Biot's theory predicts one shear wave and two longitudinal, fast and slow compressional waves. The fast compressional wave corresponds to solid and fluid moving in phase, and the slow one corresponds to solid and fluid moving in opposite phase. The Biot's theory was experimentally confirmed by the observation of the fast and slow compressional wave in glass bead samples filled with water[2].

Because of the unique properties of liquid helium [3], it is of fundamental importance to investigate the sound propagation in superfluid-filled porous media. Below the λ -transition temperature $T_{\lambda} = 2.17K$, liquid ⁴He becomes a superfluid and behaves as a "mixture" of a normal(viscous) component with mass density ρ_n and a superfluid (zero-viscosity) component with mass density ρ_s ; it is clear that $\rho_n + \rho_s = \rho_h$ where ρ_h is the mass density of superfluid ⁴He(so-called He II). It must be pointed out that the superfluid component and the normal component can not be physically separated [3]. The normal (superfluid) component fraction increases(decreases) monotonously from $\rho_n = 0$ ($\rho_s = \rho_h$) at T = 0 to $\rho_n = \rho_h(\rho_s = 0)$ at and above T_{λ} . It is important that ρ_n and ρ_s can move independently, and therefore in bulk He II the two mode of sound propagation are possible. In first sound the two fluid components oscillate in phase; and in second sound ρ_s and ρ_n oscillate in opposite phase. One of the most interesting property of He II is fourth sound mode. In fourth sound only the superfluid component moves, when the normal fluid component is locked inside a rigid porous medium by viscous forces, so that its velocity is identically zero.

Since a superfluid-filled porous medium is really a three-component system, Biot's theory is not applicable directly to this system. But, at low temperatures (T < 1.1K), when the normal fluid component fraction may be neglected, Johnson has shown that fourth sound mode is exactly a Biot's slow wave [4]. It should be noted that at low temperatures, when the mean free path of phonons and rotons becomes larger than the pore size the hydrodynamical description breaks down, so the comparison to Biot's model should be made at higher temperatures [5]. We have to point out that a number of authors extended Biot's theory in the case of two or more fluids (for review see [6],[7]). Since the fluids usually considered are not superfluids, the authors neglected some effects, which are actually important in the case of superfluids. Indeed, it is well known that in the case of ordinary fluids the fountain(and/or mechano-caloric) effect is negligible, however, in the case of a superfluid these effects are crucial. In particular, a temperature gradient produces relative motion between the two fluids in superfluids [3]. Therefore we have to distinguish between pressures with a "mechanical origin" and those with a "thermal origin", the later can only be found in superfluids [3] whereas the former can appear in any fluid. Moreover, it is important that the superfluid component and the normal component can not be physically separated. Actually He II is the fluid with additional degrees of freedom [3], but not a real mixture of two fluids.

In this paper the generalization of Biot's theory is given in the case of superfluid-saturated porous media, when all damping processes are neglected. The organization of this paper is as follows. In Section II we apply Biot formalism to bulk He II and derive some equations, which are used in Section IV. Section III and Section IV give a derivation of the equations which describe the propagation of longitudinal and shear waves in a superfluid-saturated, homogeneous and isotropic porous media. This is the main result of this paper. In Section V the formalism is applied to the most important particular case when the normal fluid component is locked inside a porous media by viscous forces. Finally, in Section VI we discuss some limits of our equations and summarize results.

2 The case of bulk He II

In this section we apply formalism developed by Biot [1],[8] to the wave processes in bulk He II. The wave processes in bulk He II is well understood [3], but Biot's formalism has the advantage that it can be generalized easily for three-component systems. Besides, in this section we derive some equations which are used later.

The basic idea is to describe the wave processes in He II in terms of "elastic deformations" of the superfluid and the normal components of He II. In this formalism the pressure with a "thermal origin" have to be considered as an "elastic" restore force as well as the pressure with a "mechanical origin". Here we present the key points of calculations, for more discussion of details of the formalism the reader is referred to [1],[8].

Let us define the displacement of the superfluid and the normal components as \vec{u}_s and \vec{u}_n respectively. Then the displacement \vec{u} of He II is [3]:

$$\vec{u} = \frac{\rho_s}{\rho_h} \vec{u}_s + \frac{\rho_n}{\rho_n} \vec{u}_n. \tag{1}$$

Following [1] we choose the Lagrangian coordinates of the system as the six displacement components $u_{sx}, u_{sy}, u_{sz}, u_{nx}, u_{ny}, u_{nz}$ of He II. Note that in contrast with ref.[1] no averaging procedure is required here. Then the kinetic energy T_h of the unit volume of He II is presented as:

$$2T_h = \sum_{x,y,z} \left(\rho_n \left[\frac{\partial u_{ni}}{\partial t} \right]^2 + \rho_s \left[\frac{\partial u_{si}}{\partial t} \right]^2 \right); \tag{2}$$

here we take into account that the superfluid component and the normal component move independently. So the mass coupling parameter between the normal component and the superfluid component equals zero [1].

Let us assume that the system is in equilibrium being at rest. Therefore, any displacement is a deviation from a state of minimum potential energy. Then the potential energy W_h per unit volume of He II is [1],[9]:

$$2W_h = \sigma_n^h \epsilon_n + \sigma_s^h \epsilon_s; \tag{3}$$

here we take into account that the shear modulus of He II is zero. We formally separate the stress of the normal component σ_n^h and the stress of the superfluid component σ_s^h (see Section III as well); they describe the pressure with a "thermal origin" as well as the pressure with a "mechanical origin". $\epsilon_s = div \ \vec{u}_s$ and $\epsilon_n = div \ \vec{u}_n$ are the strain in the normal and the superfluid components of He II respectively. From (1) the strain in the fluid ϵ is given by:

$$\epsilon = \frac{\rho_s}{\rho_h} \epsilon_s + \frac{\rho_n}{\rho_h} \epsilon_n. \tag{4}$$

When there is no (nonuniform) relative motion between the superfluid and the normal components then $\epsilon_s = \epsilon_n$ and no temperature gradients exist (see the text after equation (16)). In this case the dynamics of the system is described by the theory of elasticity.

But when $\epsilon_s \neq \epsilon_n$ temperature gradients exist and the fountain and/or mechano-caloric effect takes place (see the text after equation (16)). We show in this section that in this case the formalism of theory of elasticity is applicable as well.

In the first approximation the stress components are linear functions of the strain components, so one gets [1]:

$$\sigma_s^h = R_s^h \epsilon_s + R_{sn}^h \epsilon_n;
\sigma_n^h = R_n^h \epsilon_n + R_{sn}^h \epsilon_s;$$
(5)

 R_s^h and R_n^h describe "elastic properties" of the superfluid and the normal components, and R_{sn}^h describes the "elastic interaction" between them [1]. To make results more useful let us express R_s^h , R_n^h and R_{sn}^h in terms of

directly measurable coefficients [8].

Let us now consider a volume of He II in a vessel. First we consider the case, when none of the fluid components is allowed to escape from vessel. We shall refer to this case as "unjacketed compressibility test" (see Section III). If a pressure p is applied to He II (see Fig. 1), no relative motion between the superfluid component and the normal component takes place, i.e.:

$$\epsilon_s = \epsilon_n = \epsilon. \tag{6}$$

So, in this case temperature difference does not exist. Fluid pressure has only "mechanical origin" and we have [8]:

$$\sigma_s^h = -\frac{\rho_s}{\rho_h} p;$$

$$\sigma_n^h = -\frac{\rho_n}{\rho_h} p;$$
(7)

so, from (5) and (7) we get:

$$-\frac{\rho_s}{\rho_h}p = R_s^h \epsilon_s + R_{sn}^h \epsilon_n; -\frac{\rho_n}{\rho_h}p = R_n^h \epsilon_n + R_{sn}^h \epsilon_s;$$
(8)

Besides, in this case we have:

$$\frac{1}{K_f} = -\frac{\epsilon}{p};\tag{9}$$

where K_f is the adiabatic bulk modulus of He II.

Using (9) from (8) we get (recall that $\epsilon = \epsilon_n$, in this case):

$$R_s^h = \frac{\rho_s}{\rho_h} K_f - R_{sn}^h.$$

$$R_n^h = \frac{\rho_n}{\rho_h} K_f - R_{sn}^h.$$
(10)

Now we consider another case, when the superfluid component is allowed to escape through a superleak, but not the normal fluid component (see Fig. 2). We shall refer to this case as "second jacketed compressibility test" (see Section III). If a pressure p is applied to He II, the superfluid component passes through the superleak into the reservoir of He II. An applied external pressure squeeze out some of the superfluid component, this means that temperature increases in a vessel. So, a temperature difference between the vessel and the reservoir of He II exists. As it is well known, temperature difference between the two volumes of He II is accompanied by a pressure difference between these volumes (fountain or/and mechanocaloric effect)[3]. Since the superfluid component is allowed to pass through the superleak, its partial pressure is zero. But the normal fluid component is identified with the thermal excitations of He II (gas of phonons and rotons) and its partial pressure is not zero. Thus, if we neglect the thermal expansion coefficient of He II (which is anomalously small), we can conclude that fluid pressure in this case has only "thermal origin". It is clear that the normal fluid component pressure equals to the external pressure (let us define it in this case by p'), and we have:

$$\begin{aligned}
\sigma_s^h &= 0; \\
\sigma_n^h &= -p';
\end{aligned} \tag{11}$$

or using (5) and (11):

$$0 = R_s^h \epsilon_s + R_{sn}^h \epsilon_n;$$

-p' = $R_n^h \epsilon_n + R_{sn}^h \epsilon_s;$ (12)

Let us define the bulk modulus of the normal fluid component K_n as:

$$\frac{1}{K_n} = -\frac{\epsilon_n}{p'};\tag{13}$$

Since the superfluid component and the normal component can not be physically separated, the definition of the bulk modulus of the normal fluid component is formal. But let us point out that K_n does not enter into final equations (18), (19); so this problem is irrelevant in this case.

From (13) and (12) we have:

$$(R_{sn}^{h})^{2} + R_{s}^{h} K_{n} \left(1 - \frac{R_{n}^{h}}{K_{n}}\right) = 0.$$
(14)

Besides, in this case the energy conservation law gives:

$$-\frac{\rho_s}{\rho_h}(\epsilon_n - \epsilon_s)S\rho_h T = \rho_h C\Delta T; \qquad (15)$$

where $(\rho_s/\rho_h)(\epsilon_n - \epsilon_s)$ represents the fluid volume entering through the superleak [8]. *C* and *S* are the specific heat and the entropy per unit mass of He II, respectively. ΔT is the difference between the temperature of the fluid inside a vessel and the temperature of the reservoir of He II caused by external pressure [3]:

$$\Delta T = \frac{p'}{\rho_h S}.$$
(16)

One can see from (15) that $\Delta T = 0$ when $\epsilon_s - \epsilon_n = 0$, so pressure has only a "mechanical origin". But when $\epsilon_s \neq \epsilon_n$ from (15) one gets that $\Delta T \neq 0$, therefore temperature gradients exist.

From (15) using the first equation in (12) we can eliminate ϵ_s and ϵ_n , and we get the following expression for K_n :

$$\frac{1}{K_n} = \frac{1}{K_f} + \frac{1}{\rho_h} \frac{C}{S^2 T};$$
(17)

here we have used (10), (14), (16) and definition (13) as well.

From (10) and (14) using (17) we directly get:

$$R_{s}^{h} = K_{f} \frac{\rho_{s}^{2}}{\rho_{h}^{2}} + \frac{\rho_{h}S^{2}T}{C} \frac{\rho_{s}^{2}}{\rho_{h}^{2}};$$

$$R_{n}^{h} = K_{f} \frac{\rho_{n}^{2}}{\rho_{h}^{2}} + \frac{\rho_{h}S^{2}T}{C} \frac{\rho_{s}^{2}}{\rho_{h}^{2}};$$

$$R_{sn}^{h} = K_{f} \frac{\rho_{s}\rho_{n}}{\rho_{h}^{2}} - \frac{\rho_{h}S^{2}T}{C} \frac{\rho_{s}^{2}}{\rho_{h}^{2}}.$$
(18)

Equation (18) gives R_s^h , R_n^h and R_{sn}^h in terms of directly measurable coefficients. These relations are used in Section IV.

Now, to demonstrate the correctness of the expressions obtained above let us calculate the velocity of sound propagation in He II.

Using (2), (3) and (5) from Lagrange's equations one derives the equations for the wave propagation in He II [1]:

$$\rho_s \frac{\partial^2}{\partial t^2} \epsilon_s = \vec{\nabla}^2 (R_s^h \epsilon_s + R_{sn}^h \epsilon_n);$$

$$\rho_n \frac{\partial^2}{\partial t^2} \epsilon_n = \vec{\nabla}^2 (R_{sn}^h \epsilon_s + R_n^h \epsilon_n);$$
(19)

Solutions of (19) with \vec{k} wave vector have the form:

$$\epsilon_s = C_s \exp[i\vec{k}(\vec{r} + \vec{V}t)];$$

$$\epsilon_n = C_n \exp[i\vec{k}(\vec{r} + \vec{V}t)];$$
(20)

 C_s and C_n are real constants, and \vec{V} is the velocity of the wave.

Substituting (20) into (19) we find that there are two modes of longitudinal waves the fast and the slow waves with velocities V_1 and V_2 respectively. Using (18) we get the expressions for V_1 and V_2 :

$$V_1^2 = \frac{K_f}{\rho_h};$$

$$V_2^2 = \frac{\rho_s}{\rho_n} \frac{S^2 T}{C};$$
(21)

The fast wave corresponds to the superfluid component and the normal component moving in phase; from (19) one can see that in the case of fast wave $C_s = C_n$ [1]. This means that $\epsilon_s = \epsilon_n$, so no fountain(and/or mechano-caloric) effect takes place and only the pressure with a "mechanical origin" appear. This is a ordinary wave in an ordinary fluid (see also Section V).

The slow wave corresponds to the superfluid and the normal components moving in opposite phase. In the case of slow wave (19) gives that $\rho_s C_s + \rho_n C_n = 0$ [1]. Thus $\epsilon = 0$ and pressure with a "mechanical origin" does not appear; but $\epsilon_s \neq \epsilon_n$, thus temperature oscillations exist. This is a temperature wave which appear only in superfluids (see also Section V).

These are well known results of Landau's theory of sound propagation in He II [3]. Therefore, we have shown that the formalism developed by Biot [1] may be applied to the wave processes in He II. Besides, we conclude that bulk He II may be regarded as a fluid-saturated porous media with porosity ρ_s/ρ_h . The normal fluid component plays the role of the solid part with K_n bulk modulus and zero shear modulus, and the superfluid component plays the role of the fluid. Equation (21) shows that second sound is exactly slow wave mode.

3 Derivation of general equations

In this section we will derive the general equations which govern the propagation of longitudinal and shear waves in a superfluid-saturated, homogeneous and isotropic porous media. Let us consider a unit cube of superfluid-filled, macroscopically homogeneous and isotropic porous solid as an element. The element is assumed to be large as compared to pore sizes, but small compared to a wavelength. In this case, the element is described by the average displacement of the normal fluid component \vec{u}_n , the superfluid component \vec{u}_s , and the solid \vec{u} parts.

Following [1], let us introduce the Lagrangian viewpoint and the concept of generalized coordinates. The Lagrangian coordinates are chosen as the nine average displacement components of both the solid and the fluid i.e. $u_x, u_y, u_z, u_{sx}, u_{sy}, u_{sz}, u_{nx}, u_{ny}, u_{nz}$.

The kinetic energy T of the system per unit volume is [1]:

$$2T = \sum_{i=x,y,z} \left(\rho_{11} \left[\frac{\partial u_i}{\partial t} \right]^2 + \rho_{22}^s \left[\frac{\partial u_{si}}{\partial t} \right]^2 + \rho_{22}^n \left[\frac{\partial u_{ni}}{\partial t} \right]^2 + 2\rho_{12}^s \left[\frac{\partial u_i}{\partial t} \frac{\partial u_{si}}{\partial t} \right] + 2\rho_{12}^n \left[\frac{\partial u_i}{\partial t} \frac{\partial u_{ni}}{\partial t} \right] \right); \qquad (22)$$

here we take into account that the directions x, y, z are equivalent and uncoupled dynamically. We can express ρ_{11} , ρ_{22}^s , ρ_{12}^n , ρ_{12}^s and ρ_{12}^n in terms of directly measurable coefficients. Calculations quite similar to [1] for ρ_{11} , ρ_{22}^s , ρ_{12}^n , ρ_{12}^s , ρ_{12}^n density coefficients give (see also [4]):

$$\rho_{11} = (1 - \beta)\rho_{sol} - \rho_{12}^{s} - \rho_{12}^{n};$$

$$\rho_{22}^{s} = \beta\rho_{s} - \rho_{12}^{s};$$

$$\rho_{22}^{n} = \beta\rho_{n} - \rho_{12}^{n};$$

$$\rho_{12}^{s} = (1 - \alpha)\beta\rho_{s};$$

$$\rho_{12}^{n} = (1 - \alpha)\beta\rho_{n};$$
(23)

From (23) one can calculate ρ_{11} , ρ_{22}^s , ρ_{12}^n , ρ_{12}^s and ρ_{12}^n using the directly measurable coefficients. β is the porosity(fluid volume fraction); ρ_{sol} is the density of the solid; α is a purely geometrical quantity independent of solid and fluid densities; $\alpha = n^2$ where n is the index of refraction [4].

The $\rho_{12}^s(\rho_{12}^n)$ coefficient represents a mass coupling parameter between the solid and the superfluid(normal) components. As ρ_s and ρ_n can move independently, the mass coupling parameter between the superfluid and the normal components is identically zero.

Let us assume that system is in equilibrium being at rest, therefore any displacement is a deviation from a state of minimum potential energy. Then the potential energy W per unit volume of the system is given by [1]:

$$2W = \sigma_x e_x + \sigma_y e_y + \sigma_z e_z + \tau_x \gamma_x + \tau_y \gamma_y + \tau_z \gamma_z + \sigma_s \epsilon_s + \sigma_n \epsilon_n; \qquad (24)$$

here, the generalized procedure of the classical theory of elasticity has been used [9]. W is expressed in terms of the strain and stress components.

The stress tensor in the porous material is:

$$\begin{pmatrix} \sigma_x + \sigma_s + \sigma_n & \tau_z & \tau_y \\ \tau_z & \sigma_y + \sigma_s + \sigma_n & \tau_x \\ \tau_y & \tau_x & \sigma_z + \sigma_s + \sigma_n \end{pmatrix}$$

 $\sigma_x, \sigma_y, \sigma_z, \tau_x, \tau_y, \tau_z$ components of the stress tensor are the forces applied to the portion of the cube faces occupied by the solid. Note, that the fraction of solid area per unit cross section is $(1 - \beta)$ [1]. In stress tensor we formally separate the forces σ_s and σ_n acting respectively on the normal component and the superfluid component "parts" of each face of the cube. The "fraction" of the superfluid(normal) component area per unit cross section is $\beta \rho_s / \rho_h \quad (\beta \rho_n / \rho_h)$. Besides, $\sigma = \sigma_s + \sigma_n$; σ is the force acting on the fluid part of each face of the cube. The fraction of the fluid area per unit cross section is β .

The strain tensor in the solid is:

$$\begin{pmatrix} e_x & \frac{1}{2}\gamma_z & \frac{1}{2}\gamma_y \\ \frac{1}{2}\gamma_z & e_y & \frac{1}{2}\gamma_z \\ \frac{1}{2}\gamma_y & \frac{1}{2}\gamma_x & e_z \end{pmatrix}$$

with $e_x = \partial u_x / \partial x$ etc. and $\gamma_z = \partial u_x / \partial y + \partial u_y / \partial x$ etc.

In the first approximation the stress components are linear functions of the strain components. The stress-strain relations for superfluid-filled, statistically isotropic porous media can be expressed as [1]:

$$\sigma_{x} = 2Ne_{x} + Ae + Q_{s}\epsilon_{s} + Q_{n}\epsilon_{n};$$

$$\sigma_{y} = 2Ne_{y} + Ae + Q_{s}\epsilon_{s} + Q_{n}\epsilon_{n};$$

$$\sigma_{z} = 2Ne_{z} + Ae + Q_{s}\epsilon_{s} + Q_{n}\epsilon_{n};$$

$$\tau_{x} = N\gamma_{x}; \ \tau_{y} = N\gamma_{y}; \ \tau_{z} = N\gamma_{z};$$

$$\sigma_{s} = Q_{s}e + R_{s}\epsilon_{s} + R_{sn}\epsilon_{n};$$

$$\sigma_{n} = Q_{n}e + R_{sn}\epsilon_{s} + R_{n}\epsilon_{n};$$
(25)

where

$$e = e_x + e_y + e_z$$

Note that, because of (25) describes elastic properties of coupled system of the porous solid and He II, the coefficients R_s , R_n , R_{sn} differ from R_s^h , R_n^h , R_{sn}^h . But the relations derived in Section II are still satisfied. Indeed, it is clear that one can consider porous solid as a vessel. So, we can identify "unjacketed compressibility test" and "second compressibility test" in Section II with the unjacketed compressibility test and the second jacketed compressibility test considered in the next section respectively. In Section IV we use some of the relations derived in Section II.

It should be pointed out that thermodynamic parameters of He II in the porous media and the ones of bulk He II may differ from each other (ρ_n for example) [3].

The thermal expansion coefficient of He II is too small and we can neglect it. Besides, we neglect the heat exchange between the solid and He II. This is a reasonable assumption if the wave frequency is not too small. Under this assumptions it is clear that between the solid and He II forces caused by temperature gradients do not exist. So, forces between the solid and He II have "mechanical origin". The two last terms in the first equation from (25), for instance, describe the interaction of the superfluid component and the normal component with the solid [1]. Because of He II interacts with the porous solid "as a whole" we have:

$$Q_s \epsilon_s + Q_n \epsilon_n = Q \epsilon;$$

and using (4) one gets:

$$Q_s = \frac{\rho_s}{\rho_h} Q; \quad Q_n = \frac{\rho_n}{\rho_h} Q; \tag{26}$$

Now we are ready to write down the general wave equations. The calculations following the procedure of ref.[1] gives the equations for the wave propagation in a superfluid-saturated porous media. Using (22),(25) and (26) from Lagrange's equations we derive:

$$N\vec{\nabla}^{2}\vec{u} + (A+N)\vec{\nabla}e + \frac{\rho_{s}}{\rho_{h}}Q\vec{\nabla}\epsilon_{s} + \frac{\rho_{n}}{\rho_{h}}Q\vec{\nabla}\epsilon_{n} =$$

$$= \frac{\partial^{2}}{\partial t^{2}}(\rho_{11}\vec{u} + \rho_{12}^{s}\vec{u}_{s} + \rho_{12}^{n}\vec{u}_{n});$$

$$\frac{\rho_{s}}{\rho_{h}}Q\vec{\nabla}e + R_{s}\vec{\nabla}\epsilon_{s} + R_{sn}\vec{\nabla}\epsilon_{n} = \frac{\partial^{2}}{\partial t^{2}}(\rho_{12}^{s}\vec{u} + \rho_{22}^{s}\vec{u}_{s});$$

$$\frac{\rho_{n}}{\rho_{h}}Q\vec{\nabla}e + R_{n}\vec{\nabla}\epsilon_{n} + R_{sn}\vec{\nabla}\epsilon_{s} = \frac{\partial^{2}}{\partial t^{2}}(\rho_{12}^{n}\vec{u} + \rho_{22}^{n}\vec{u}_{n});$$
(27)

here $\vec{\nabla}$ is the nabla operator.

Because of the statistical isotropy of the material, the rotational waves are separated from the longitudinal waves and obey independent equations of propagation [1].

Applying the divergence operator to the set of equations (27) we obtain:

$$\vec{\nabla}^{2} \left(Pe + \frac{\rho_{s}}{\rho_{h}} Q\epsilon_{s} + \frac{\rho_{n}}{\rho_{h}} Q\epsilon_{n} \right) = \frac{\partial^{2}}{\partial t^{2}} (\rho_{11}e + \rho_{12}^{s}\epsilon_{s} + \rho_{12}^{n}\epsilon_{n});$$

$$\vec{\nabla}^{2} \left(\frac{\rho_{s}}{\rho_{h}} Qe + R_{s}\epsilon_{s} + R_{sn}\epsilon_{n} \right) = \frac{\partial^{2}}{\partial t^{2}} (\rho_{12}^{s}e + \rho_{22}^{s}\epsilon_{s});$$

$$\vec{\nabla}^{2} \left(\frac{\rho_{n}}{\rho_{h}} Qe + R_{sn}\epsilon_{s} + R_{n}\epsilon_{n} \right) = \frac{\partial^{2}}{\partial t^{2}} (\rho_{12}^{n}e + \rho_{22}^{n}\epsilon_{n}); \qquad (28)$$

with

P = A + 2N

Equations (28) govern the propagation of longitudinal waves.

Applying the *rot* operator to equations (27) we obtain:

$$N\vec{\nabla}^{2}\vec{\omega} = \frac{\partial^{2}}{\partial t^{2}}(\rho_{11}\vec{\omega} + \rho_{12}^{s}\vec{\omega}_{s} + \rho_{12}^{n}\vec{\omega}_{n});$$

$$0 = \frac{\partial^{2}}{\partial t^{2}}(\rho_{12}^{s}\vec{\omega} + \rho_{22}^{s}\vec{\omega}_{s});$$

$$0 = \frac{\partial^{2}}{\partial t^{2}}(\rho_{12}^{n}\vec{\omega} + \rho_{22}^{n}\vec{\omega}_{n});$$
(29)

with the definitions

$$\vec{\omega} = rot \ \vec{u}; \quad \vec{\omega}_s = rot \ \vec{u}_s; \quad \vec{\omega}_n = rot \ \vec{u}_n;$$

Equations (29) govern the propagation of pure rotational(shear) waves.

When $\rho_s = 0$ or $\rho_n = 0$ equations (28), (29) reduces to the set of equations obtained by Biot [1]. Besides when $\beta = 1$ and $K_B = N = 0$ (the case of bulk He II) (28), (29) reduce to (19).

Equations (28),(29) describe the propagation of longitudinal and shear waves in a superfluid-saturated, homogeneous and isotropic porous media in the long wavelength limit when all damping processes are neglected.

Note that using results the of [1] and [5] one can easily incorporate the effect of the wave attenuation due to finite viscousity of the normal component in these equations.

4 Calculation of the coefficients

To make the theory useful we must express coefficients $N, A, Q, R_s, R_n, R_{sn}$ in terms of directly measurable ones [8].

The coefficient N represents the shear modulus of the bulk material, which is directly measurable. A, Q, R_s, R_n, R_{sn} can be expressed in terms of directly measurable coefficients by considering three compressibility tests. In the absence of electrochemical interfacial effect between fluid and solid A, Q, R_{sn}, R_s, R_n and N are independent of what fluid is in the pores, including vacuum [4]; we assumed this through this paper.

In the "unjacketed" compressibility test, a sample of the material is immersed in a fluid to which a pressure p is applied (see Fig. 3). Then the adiabatic bulk modulus of solid K_S is determined by:

$$\frac{1}{K_S} = -\frac{e}{p}.$$
(30)

In this case (6) takes place, thus fluid pressure has only "mechanical origin" and in (25) we have [8]:

$$\sigma_x = \sigma_y = \sigma_z = -(1 - \beta)p;$$

$$\sigma_s = -\beta \frac{\rho_s}{\rho_h} p;$$

$$\sigma_n = -\beta \frac{\rho_n}{\rho_h} p.$$
(31)

And from (25),(26) and (31) we get:

$$-(1-\beta)p = \frac{2}{3}Ne + Ae + \frac{\rho_s}{\rho_h}Q\epsilon_s + \frac{\rho_n}{\rho_h}Q\epsilon_n;$$

$$-\beta\frac{\rho_s}{\rho_h}p = \frac{\rho_s}{\rho_h}Qe + R_s\epsilon_s + R_{sn}\epsilon_n;$$

$$-\beta\frac{\rho_n}{\rho_h}p = \frac{\rho_n}{\rho_h}Qe + R_{sn}\epsilon_s + R_n\epsilon_n;$$
(32)

Using (30) from (32) we get:

$$K_S = \frac{(A + (2/3)N) Z_1 - Q^2 Z_2}{(1 - \beta)Z_1 - \beta Q Z_2};$$
(33)

where

$$Z_{1} = R_{s}R_{n} - (R_{sn})^{2};$$

$$Z_{2} = \frac{\rho_{s}^{2}}{\rho_{h}^{2}}R_{n} - 2\frac{\rho_{s}\rho_{n}}{\rho_{h}^{2}}R_{sn} + \frac{\rho_{n}^{2}}{\rho_{h}^{2}}R_{s};$$
(34)

Besides, (30) and the two last equations from (32) give:

$$R_{s} = \left(\beta - \frac{Q}{K_{S}}\right) \frac{\rho_{s}}{\rho_{h}} K_{f} - R_{sn};$$

$$R_{n} = \left(\beta - \frac{Q}{K_{S}}\right) \frac{\rho_{n}}{\rho_{h}} K_{f} - R_{sn};$$
(35)

here we have used (6) and (9) as well.

In the first "jacketed" compressibility test, a sample of the material is enclosed in a thin impermeable jacket and then subjected to an external fluid pressure p. The fluid inside the jacket can escape through a tube in the reservoir of He II (see Fig. 4), so the fluid pressure is exactly zero. The adiabatic bulk modulus of the skeletal frame K_B is:

$$\frac{1}{K_B} = -\frac{e}{p};\tag{36}$$

and in (25) we have [8]:

$$\sigma_x = \sigma_y = \sigma_z = -p;$$

$$\sigma_s = \sigma_n = 0.$$
(37)

And from (25),(26) and (37) we have:

$$p = \frac{2}{3}Ne + Ae + \frac{\rho_s}{\rho_h}Q\epsilon_s + \frac{\rho_n}{\rho_h}Q\epsilon_n;$$

$$0 = \frac{\rho_s}{\rho_h}Qe + R_s\epsilon_s + R_{sn}\epsilon_n;$$

$$0 = \frac{\rho_n}{\rho_h}Qe + R_{sn}\epsilon_s + R_n\epsilon_n;$$
(38)

Using (36) from (38) we get:

$$K_B = \frac{(A + (2/3)N)Z_1 - Q^2 Z_2}{Z_1};$$
(39)

where Z_1 and Z_2 are given by (34).

In the second "jacketed" compressibility test only the superfluid component is allowed to escape through a superleak in the reservoir of He II (see Fig. 5). An applied external pressure squeeze out some of the superfluid component; so the temperature of He II in the pores increases and mechanocaloric effect [3] takes place. In this case the bulk modulus of the skeletal frame with the normal fluid component K_H is defined by:

$$\frac{1}{K_H} = -\frac{e}{p}.\tag{40}$$

Since only the superfluid component is allowed to escape through the superleak, the effective frame here includes both the solid and the normal fluid component. Because of the superfluid component and the normal component can not be physically separated, the definition of the bulk modulus of the effective frame is formal. But let us point out that K_H does not enter into final equations (44); so this problem is irrelevant in this case.

Let us note again that we neglect the heat exchange between the porous solid and He II. In general this is not the case. But recall that we consider the wave processes in a porous medium. And, if the wave frequency is not too small, the heat exchange between the porous solid and He II during times of order of the wave period is negligible (adiabatic process). Besides, we neglect the thermal expansion coefficient of He II (see Section II). So, the response of the sample on the external pressure p simply is a sum of the purely "mechanical response" of the solid and the purely "thermal response" of the normal fluid component. Thus, we can represent the external pressure as follows: $p = (p - \beta p') + \beta p'$. The first term in this sum corresponds to the purely "mechanical response" of the solid, and the second term in this sum corresponds to the purely "thermal response" of the normal fluid component. In this case in (25) we have:

$$\sigma_z = \sigma_y = \sigma_z = -(1 - \beta')p;$$

$$\sigma_s = 0;$$

$$\sigma_n = -\beta'p;$$
(41)

here $\beta' = \beta(p'/p)$ is the measure of the "thermal response" of the effective frame. If we neglect the mechano-caloric effect $\beta' = 0$ and this case reduces to the first compressibility test.

From (25),(26) and (41) we get:

$$-(1-\beta')p = \frac{2}{3}Ne + Ae + \frac{\rho_s}{\rho_h}Q\epsilon_s + \frac{\rho_n}{\rho_h}Q\epsilon_n;$$

$$0 = \frac{\rho_s}{\rho_h}Qe + R_s\epsilon_s + R_{sn}\epsilon_n;$$

$$-\beta'p = \frac{\rho_n}{\rho_h}Qe + R_{sn}\epsilon_s + R_n\epsilon_n;$$
(42)

Using (40) and two last equations from (42) we can write:

$$0 = -\frac{\rho_s}{\rho_h} Q \frac{p}{K_H} + R_s \frac{R_{sn}^h}{R_s^h} \frac{p'}{K_n} - R_{sn} \frac{p'}{K_n};$$

$$-\beta'p = -\frac{\rho_n}{\rho_h}Q\frac{p}{K_H} + R_{sn}\frac{R_{sn}^h}{R_s^h}\frac{p'}{K_n} - R_n\frac{p'}{K_n};$$
 (43)

here we have used (13) and (12) as well.

Finally (33),(39) with (35),(43) and (17),(18) directly give:

$$A = \frac{(1-\beta)(1-\beta-(K_B/K_S))+\beta(K_S/K_f)K_B}{1-\beta-(K_B/K_S)+\beta(K_S/K_f)} - \frac{2}{3}N;$$

$$Q = \frac{(1-\beta-(K_B/K_S))\beta K_S}{1-\beta-(K_B/K_S)+\beta(K_S/K_f)};$$

$$R_s = \frac{\beta^2 K_S}{1-\beta-(K_B/K_S)+\beta(K_S/K_f)}\frac{\rho_s^2}{\rho_h^2} + \beta\frac{\rho_h S^2 T}{C}\frac{\rho_s^2}{\rho_h^2};$$

$$R_n = \frac{\beta^2 K_S}{1-\beta-(K_B/K_S)+\beta(K_S/K_f)}\frac{\rho_h^2}{\rho_h^2} + \beta\frac{\rho_h S^2 T}{C}\frac{\rho_s^2}{\rho_h^2};$$

$$R_{sn} = \frac{\beta^2 K_S}{1-\beta-(K_B/K_S)+\beta(K_S/K_f)}\frac{\rho_s \rho_n}{\rho_h^2} - \beta\frac{\rho_h S^2 T}{C}\frac{\rho_s^2}{\rho_h^2};$$
(44)

where K_f, K_S, K_B and N are the directly measurable coefficients. This is the desired result.

When $\rho_s = 0$ or $\rho_n = 0$, (44) reduces to the set of equations obtained by Biot and Willis [8]. Besides, when $\beta = 1$ and $K_B = N = 0$ (the case of bulk He II), equation (44) reduces to (18).

5 Particular solutions

Equations (28) and (29) describe the propagation of longitudinal and shear waves in a superfluid-saturated, homogeneous and isotropic porous media in the long wavelength limit when all damping processes are neglected. The general solutions of these equations will be discussed elsewhere. Here, we consider only the most important particular solutions when

$$\vec{u} = \vec{u}_n. \tag{45}$$

Physically this means that the normal fluid component is locked inside a porous medium by viscous forces and therefore there is no relative motion between the normal fluid component and the porous solid. This case is realized in high-porosity aerogels, for example. Because of (45) we added together the first and last equations of (28). Then, we obtain:

$$\vec{\nabla}^{2} \left([P + 2\frac{\rho_{n}}{\rho_{h}}Q + R_{n}]e + [\frac{\rho_{s}}{\rho_{h}}Q + R_{sn}]\epsilon_{s} \right) =$$

$$= \frac{\partial^{2}}{\partial t^{2}} \left([\rho_{11} + 2\rho_{12}^{n} + \rho_{22}^{n}]e + \rho_{12}^{s}\epsilon_{s} \right);$$

$$\vec{\nabla}^{2} \left([\frac{\rho_{s}}{\rho_{h}}Q + R_{sn}]e + R_{s}\epsilon_{s} \right) = \frac{\partial^{2}}{\partial t^{2}} \left(\rho_{12}^{s}e + \rho_{22}^{s}\epsilon_{s} \right). \tag{46}$$

Similarly, from (29) and (45) we obtain:

$$N\vec{\nabla}^{2}\vec{\omega} = \frac{\partial^{2}}{\partial t^{2}} \left(\left[\rho_{11} + 2\rho_{12}^{n} + \rho_{22}^{n} \right] \vec{\omega} + \rho_{12}^{s} \vec{\omega}_{s} \right); \\ 0 = \frac{\partial^{2}}{\partial t^{2}} \left(\rho_{12}^{s} \vec{\omega} + \rho_{22}^{s} \vec{\omega}_{s} \right).$$
(47)

Equations (46) and (47) describe the propagation of longitudinal and shear waves respectively, when the normal fluid component is locked inside a porous solid.

It is convenient to introduce the following definitions:

$$P' = P + 2\frac{\rho_n}{\rho_h}Q + R_n;$$

$$Q' = \frac{\rho_s}{\rho_h}Q + R_{sn};$$

$$\rho' = \rho_{11} + 2\rho_{12}^n + \rho_{22}^n.$$
(48)

Let us consider equations (46) for the longitudinal waves. The solutions of these equations with \vec{k} wave vector are written in the form

$$e = C_1 \exp[i\vec{k}(\vec{r} + \vec{V}t)];$$

$$\epsilon_s = C_2 \exp[i\vec{k}(\vec{r} + \vec{V}t)];$$
(49)

where \vec{V} is the velocity of these waves; C_1 and C_2 are real constants. The velocity \vec{V} is determined by substituting (49) into (46). There are two modes of longitudinal waves: the fast and the slow waves, with V_f and V_s velocities respectively [1]. The velocities of propagation $V_{f,s}$ of fast and slow waves are given by:

$$V_{f,s}^{2} = \frac{G \pm \left[G^{2} - 4\left(\rho'\rho_{22}^{s} - (\rho_{12}^{s})^{2}\right)\left(P'R_{s} - (Q')^{2}\right)\right]^{\frac{1}{2}}}{2\left(\rho'\rho_{22}^{s} - (\rho_{12}^{s})^{2}\right)};$$
(50)

with

$$G = P'\rho_{22}^s + R_s\rho' - 2Q'\rho_{12}^s;$$

The fast wave corresponds to the solid with locked normal fluid component and the superfluid component moving in phase, and the slow wave corresponds to solid with locked normal fluid component and the superfluid component moving in opposite phase. Using the formula (50) we examine the dependence of $V_{f,s}$ upon the temperature. In Fig. 6, Fig. 7 and Fig. 8 fast and slow wave velocities as a function of temperature are presented for porosities 0.7, 0.98 and 0.99 respectively (see Section VI for discussion).

From (46) for fast and slow wave amplitudes we have [1]:

$$C_{2f,s} = -D_{f,s}C_{1f,s}; (51)$$

where

$$D_{f,s} = \frac{V_{f,s}^2 \ \rho' \ - \ P'}{V_{f,s}^2 \ \rho_{12}^s \ - \ Q'};$$

Using (15) from (49) and (51) we can write down expression for temperature gradient oscillations (recall that $\epsilon_n = e$, in this case):

$$\Delta T_{f,s} = (\Delta T_{f,s})_{max} \exp[i\vec{k}(\vec{r} + \vec{V}_{f,s}t) + i\pi]; \qquad (52)$$

where

$$(\Delta T_{f,s})_{max} = C_{1\,f,s} \left(1 + D_{f,s}\right) \frac{\rho_s}{\rho_h} \frac{ST}{C};$$

 $(\Delta T_{f,s})_{max}$ is the temperature oscillations amplitude. The sign of $(\Delta T_{f,s})_{max}$ determines the relative phase of $\Delta T_{f,s}$ and e (see equations (49) and (52)). If $(\Delta T_{f,s})_{max}$ is positive, $\Delta T_{f,s}$ and e oscillate with opposite phase; and if $(\Delta T_{f,s})_{max}$ is negative, $\Delta T_{f,s}$ and e oscillate in phase. It must be noted that $(\Delta T_s)_{max}$ is always positive; $(\Delta T_f)_{max}$ can be positive or negative.

Using the formula (52) we examine the dependence of $(\Delta T_{f,s})_{max}$ upon the temperature. In Fig. 6, Fig. 7 and Fig. 8 temperature oscillations amplitudes for fast and slow waves as a function of temperature are presented for porosities 0.7, 0.98 and 0.99 respectively (see Section VI for discussion). We see that $(\Delta T_f)_{max}$ is positive in Fig. 6, but is negative in Fig. 7 and Fig. 8.

It is interesting that, in contrast with bulk He II (see Section II), even for fast wave $\epsilon_s \neq \epsilon_n (= e)$ [1] in general. So, fast wave as well as slow wave is accompanied by temperature oscillations in general. In the case of bulk He II, when $\beta = 1$ and $K_B = N = 0$, equation (52) gives that $\Delta T_f \equiv 0$; so temperature oscillations do not accompany first sound, as we have expected (see Section II).

Let us now consider equations (47) for the shear waves. From (47) it is easy to see that there is only one type of shear wave [1]. The velocity of propagation of these waves V_{sh} is

$$V_{sh} = \left[\frac{N}{\rho' \left(1 - (\rho_{12}^s)^2 / (\rho' \rho_{22}^s)\right)}\right]^{\frac{1}{2}}.$$
(53)

Using the formula (53) we examine the dependence of V_{sh} upon the temperature. In Fig. 6, Fig. 7 and Fig. 8 the shear wave mode velocity as a function of temperature is presented for porosities 0.7, 0.98 and 0.99 respectively (see Section VI for discussion).

Note that, as $\rho_{12}^s \neq 0$, the rotation of the solid with locked normal fluid component $\vec{\omega}$ is coupled to the rotation of the superfluid component $\vec{\omega}_s$ according to the relation

$$\vec{\omega}_s = -\frac{\rho_{12}^s}{\rho_{22}^s}\vec{\omega};\tag{54}$$

and therefore, $\vec{\omega}_s \neq 0$ [1]. Equation (54) shows that the rotation of the solid with locked normal fluid component and the superfluid component are in the same direction.

Equations (50) and (53) give the velocities of propagation of longitudinal and shear waves in a superfluid-saturated porous media, when the normal fluid component is locked inside the porous solid. If K_f, K_S, K_B and Nwill be measured, then one can determine the velocities of propagation of fast, slow and shear waves from (50) and (53). It should be noted that equations (50) and (53) differ from the equations obtained by Biot [1] and contain significant new physics. Indeed, Biot's results do not contain forces caused by temperature gradients. In fact, in the case of superfluid-filled porous media Biot's results are not valid. Johnson [4] has shown that in the rigid frame at low temperatures (T < 1.1K) fourth sound is exactly Biot's slow wave. However, at low temperatures the hydrodynamical description breaks down [3] and comparison to Biot's model should be made at higher temperatures [5]. So, we conclude that in all physically interesting cases Biot's equations are not applicable to superfluid-filled porous media.

Examples of physical systems to which equations (50) and (53) can be applied are superleak of porous vycor glass and high-porosity aerogels (e.g. silica aerogels with porosities $\beta > 0.9$). Superleak of porous vycor glass corresponds to a superfluid-solid system in the rigid frame limit ($K_f \ll$ K_S, K_B, N). The most interesting physical system, high-porosity aerogel, corresponds to a superfluid-solid system in the weak frame limit($K_B, N \ll K_S, K_f$).

6 Discussion and conclusions

Now, let us discuss the results obtained in the previous sections. In Section III and Section IV we derived the general equations (28),(29). These equations describe the propagation of longitudinal and shear wave in a superfluid-saturated porous media when all damping processes are neglected. Equations (28) and (29) depend explicitly on the directly measurable parameters of the porous solid and He II via relations (23) and (44). Equations (28), (29) and (23), (44) reduce to the equations obtained by Biot [1],[8] when $\rho_s = 0$ or $\rho_n = 0$. Besides, when $\beta = 1$; $K_b = N = 0$ these equations describe the sound propagation in bulk He II. From what one concludes that these equations reduce correctly to Biot's theory [1] and Landau's theory of sound propagation in bulk He II [3].

In Section V, we considered the case when the normal fluid component is locked inside a porous media by viscous forces. It is shown that in this case one shear wave and two longitudinal, fast and slow, waves exist. The velocities of these waves V_f , V_s , V_{sh} are obtained.

Since equations (46) and (47) include pressures caused by thermal gradients, they are more general in comparison with equations derived by Biot. The only case when (46) and (47) reduce to the Biot's equations is $\rho_n = 0$ (see also Section V).

Using (50), (52) and (53) we have plotted the examples of the wave velocities and temperature oscillations amplitudes for fast and slow waves as a function of temperature. In Fig. 6, Fig. 7 and Fig. 8 the plots are presented for porosities 0.7, 0.98 and 0.99 respectively.

The bulk modulus and the mass density of the solid we choose arbitrarily as $K_S = 4.07 \cdot 10^{10} N/m^2$ and $\rho_{sol} = 4 \cdot 10^3 kg/m^3$. For the bulk modulus of the skeletal frame K_B we have used the following relation $K_B = (1-\beta)^{3.5} K_S$ [10]. Poisson's ratio of the skeletal frame is assumed to be 0.2, thus for the shear modulus of the solid we have $N = (3/4)K_B$. When the porosity is not small α is given by $\alpha = 2 - \beta$ [4].

In the present paper the parameters of bulk He II [11] are used for numerical estimations. But we note that the thermodynamic parameters of HeII in the porous media and the ones of bulk HeII may differ from each other $(\rho_n \text{ for example})$ [3].

Figure 6 shows the behaviour of the fast, slow and shear wave velocities as a function of temperature for porosity $\beta = 0.7$. Moreover, the temperature oscillations amplitudes for fast and slow waves $(\Delta T_f)_{max}$ and $(\Delta T_s)_{max}$ are presented as well. In this paper we have assumed that the temperature oscillations amplitude is about ~ 0.1K, so for C_{1f} and C_{1s} we choose $C_{1f} = 1$ and $C_{1s} = 3 \cdot 10^{-3}$.

The plots presented in Fig. 6 are typical for $\beta < 0.9$. For these porosities $K_f \ll K_S, K_B, N$; so we have a superfluid-solid system in the rigid frame limit. In this limit the fast wave and shear wave velocities decrease when porosity increases. Besides, the slow wave mode is exactly fourth sound. We can show this even analytically.

In the limit of the rigid frame the expressions (50) for the fast and slow wave are greatly simplified. In this case $K_f \ll K_S, K_B, N$ and therefore

$$V_{f}^{2} = \left[\frac{K_{B} + (4/3)N}{(1-\beta)\rho_{sol} + \beta\rho_{h} - (1/\alpha)\beta\rho_{s}}\right];$$

$$V_{s}^{2} = \frac{1}{\alpha} \left(\frac{\rho_{s}}{\rho_{h}}V_{1}^{2} + \frac{\rho_{n}}{\rho_{h}}V_{2}^{2}\right);$$
(55)

here V_1 and V_2 are given by (21).

The slow wave corresponds only to the oscillation of the superfluid component (rigid frame) and V_s is the well-known velocity of fourth sound [3] renormalized by the tortuous, branching path of pore space [4]; i.e. fourth sound is exactly Biot's slow mode.

In the limit $T \to 0$ when there is no the normal fluid component and we have $(\rho_s/\rho_h) = 1$, equations (55) are identical to the corresponding expressions obtained in ref.[4].

We see from Fig. 6 that in the fast wave mode $(\Delta T_f)_{max} > 0$ in the limit of rigid frame. In the slow wave mode always $(\Delta T_s)_{max} > 0$ (see Fig. 6, Fig. 7 and Fig. 8). In addition let us note that, in contrast with V_f and V_{sh} , slow wave velocity V_s does not depend on ρ_{sol} , K_B and N.

In Fig. 7 and Fig. 8 we present behaviour of the fast, slow and shear wave velocities as a function of temperature for porosities $\beta = 0.98$ and $\beta = 0.99$ respectively. Moreover, the temperature oscillations amplitudes for fast and slow waves $(\Delta T_f)_{max}$ and $(\Delta T_s)_{max}$ are presented as well. For C_{1f} and C_{1s} we choose $C_{1f} = 10^{-1}$ and $C_{1s} = 3 \cdot 10^{-1}$.

The plots presented in Fig. 7 and Fig. 8 are typical for $\beta > 0.9$. For these porosities $K_B, N \ll K_S, K_f$; so we have a superfluid-solid system in

the weak frame limit. In this limit, in contrast with $\beta < 0.9$ (rigid frame), the slow wave velocity V_s depends on ρ_{sol} , K_B and N.

Fig. 7 shows that V_s is less compared with fourth sound velocity, but still is larger than second sound velocity.

In Fig. 8 we see that the behaviour of V_s near T_{λ} is almost the same as in Fig. 7. But at low temperatures V_s becomes considerably less than second sound velocity. For porosities $\beta > 0.99$ slow wave velocity V_s increases smoothly when β increases; and when porosity reaches $\beta = 1$ the slow wave mode is exactly second sound.

Fast wave velocity V_f decreases when the porosity increases for $\beta < 0.95$ (it becomes even less than first sound velocity); and V_f increases when the porosity increases for $\beta > 0.95$. In Fig. 7 and Fig. 8 V_f is less than first sound velocity. For $\beta = 1$ fast wave is exactly first sound. The shear wave mode velocity V_{sh} decreases when the porosity increases. Note that in Fig. 7 and Fig. 8 V_{sh} is less than V_s . For $\beta = 1$ the shear wave velocity is zero.

From Fig. 7 and Fig. 8 we can see that in the fast wave mode $(\Delta T_f)_{max} < 0$ in the limit of weak frame. When porosity is exactly $\beta = 1$ (the case of bulk He II), the temperature oscillations amplitude in the fast wave mode is zero (also see Section V).

The limit of weak frame is the most interesting and important application of our theory. Indeed, in recent years the investigation of the behaviour of superfluids in aerogels has attached increasing attention (for example, see [12],[13],[14]). Aerogels are highly open porous solids with porosities $\beta > 0.9$ (e.g. silica aerogels). The mean pore diameter in aerogels is about 20nm, so the normal fluid component is clamped in the frame by viscous forces. Besides, high-porosity aerogels have very small bulk and shear modulus and are highly compliant. That is why in the superfluid-filled aerogels pressures caused by thermal gradients play a crucial role, in contrast to other porous solids. Thus, one should describe wave processes in high-porosity aerogels using equations (46) and (47).

We point out that the theory of sound propagation in aerogels has been developed in ref.[12]. These authors modified the conventional two fluid hydrodynamic equations and derived an expression (see equation (8) in ref.[12]) which gives the longitudinal wave velocity in superfluid-filled aerogels, but does not give the shear wave velocity. It must be noted that equation (8) in ref.[12] is incorrect. To show this we remark the following.

The longitudinal wave velocity in any solid (in aerogel in the case of ref.[12]) is given by $[(K_a + (4/3)N_a) / \rho_a]^{1/2}$; [15]. Here K_a , N_a and ρ_a are the bulk modulus, the shear modulus and the mass density of the solid,

respectively. In [12] the term $(4/3)N_a/\rho_a$ is omitted (see the equation (5) in ref.[12]). This is justified if $N_a/K_a \ll 1$. In the case of aerogels Poisson's ratio equals ~ 0.2 and is independent of density [16],[10]. This means that $N_a/K_a \sim 1$ and the term $(4/3)N_a/\rho_a$ in the longitudinal wave velocity is not negligible.

Besides, in the limit $\rho_a \to \infty$ equation (8) in ref.[12] suggests that in the superfluid-filled porous media one of the modes of sound propagates with velocity C_a , where C_a is given by equation (5) in ref.[12], which is incorrect (see [15]).

In conclusion, we have derived the general equations which describe the propagation of longitudinal and shear waves in a superfluid-filled, homogeneous and isotropic porous media in the long wavelength limit when all damping processes are neglected. The most important case when the normal fluid component is locked inside a porous media by viscous forces is investigated in detail. It is shown that, in this case, one type of shear wave and two types of longitudinal, fast and slow wave, propagation are possible. The velocities of these waves are obtained. Our results reduce to the well-known equations in the appropriate limits. We have also demonstrated that the formalism developed by Biot may be applied to the wave processes in He II. It is shown that fourth sound, as well as second sound in bulk He II is exactly Biot's slow wave. In addition, we remark that the results derived in this paper may be applied to the porous media saturated with superfluid ³He as well.

References

- [1] A.M.Biot, J. Acoust. Soc. Am., 28, 168 (1956); 28, 179 (1956).
- [2] T.J.Plona, Appl. Phys. Lett., **36**, 259 (1980).
- [3] D.R.Tilley, J.Tilley, Superfluidity and Superconductivity, IOP Publishing, Bristol (1996).
- [4] D.L.Johnson, Appl. Phys. Lett., **37**, 1065 (1980).
- [5] K.Warner, J.R.Beamish, Phys.Rev.B, 50, 15896 (1994).
- [6] J.G.Berryman, "Waves In Partially Saturated Porous Media" in *Wave Propagation and Inversion*, edited by W.E.Fitzgibbon and M.F.Wheeler, SIAM, Philadelpia (1992).
- [7] M.Sahimi, Rev.Mod.Phys., **65**, 1393 (1993).
- [8] A.M.Biot, D.J.Willis, J. Appl. Mech., 24, 594 (1957).
- [9] A.M.Biot, J. Appl. Phys., 26, 182 (1955).
- [10] T.Campbell *et al.*, Phys. Rev. Lett., **82**, 4018 (1999).
- [11] J.Maynard, Phys. Rev. B, 14, 3868 (1976).
- [12] M.J.Mckenna, T.Slawecki, J.D.Maynard, Phys. Rev. Lett., 66, 1878 (1991).
- [13] D.T.Sprague et al., Phys.Rev.Lett., 77, 4568 (1996).
- [14] A.Golov *et al.*, Phys.Rev.Lett., **82**, 3492 (1999).
- [15] L.D.Landau, E.M.Lifshitz, *Theory of Elasticity*, Pergamon Press, New York, (1970).
- [16] for example see http://eande.lbl.gov/ECS/aerogels/saprops.htm

FIGURE CAPTIONS :

Fig. 1. The "unjacketed compressibility test" for bulk He II. A pressure p is applied to a volume of He II in a vessel. In this case none of the fluid components is allowed to escape from vessel.

Fig. 2. The "second jacketed compressibility test" for bulk He II. A pressure p' is applied to He II in a vessel. The applied external pressure squeeze out some of the superfluid component through the superleak into the reservoir of He II. As a consequence temperature difference between the fluid in the vessel and the reservoir of He II exists.

Fig. 3. The "unjacketed" compressibility test. A pressure p is applied to a sample of the superfluid-filled porous solid. In this case none of the fluid components is allowed to escape into the reservoir of He II.

Fig. 4. The first "jacketed" compressibility test. A pressure p is applied to a sample of the superfluid-filled porous solid. The applied external pressure squeeze out some of the fluid through the tube into the reservoir of He II. In this case both of the fluid components are allowed to escape into the reservoir of He II. Thus, no temperature difference between the superfluid in the porous solid and the reservoir of He II exists.

Fig. 5. The second "jacketed" compressibility test. A pressure p is applied to a sample of the superfluid-filled porous solid. The applied external pressure squeeze out some of the superfluid component through the super-leak into the reservoir of He II. In this case only the superfluid component is allowed to escape into the reservoir of He II. As a consequence temperature difference between the superfluid in the porous solid and the reservoir of He II exists.

Fig. 6. The velocities and the temperature oscillations amplitudes as a function of temperature for fast and slow waves; and the shear wave velocity as a function of temperature. $\beta = 0.7$, $C_{1f} = 1$ and $C_{1s} = 0.003$; $K_S = 4.07 \cdot 10^{10} N/m^2$ and $\rho_{sol} = 4 \cdot 10^3 kg/m^3$; $K_B = (1 - \beta)^{3.5} K_S$ and $N = (3/4)K_B$; $\alpha = 2 - \beta$. Here the parameters of bulk He II are used for numerical estimations.

Fig. 7. The velocities and the temperature oscillations amplitudes as a function of temperature for fast and slow waves; and the shear wave velocity as a function of temperature. $\beta = 0.98$, $C_{1f} = 0.1$ and $C_{1s} = 0.3$; $K_S = 4.07 \cdot 10^{10} N/m^2$ and $\rho_{sol} = 4 \cdot 10^3 kg/m^3$; $K_B = (1 - \beta)^{3.5} K_S$ and $N = (3/4)K_B$; $\alpha = 2 - \beta$. Here the parameters of bulk He II are used for numerical estimations.

Fig. 8. The velocities and the temperature oscillations amplitudes as a function of temperature for fast and slow waves; and the shear wave velocity as a function of temperature. $\beta = 0.99$, $C_{1f} = 0.1$ and $C_{1s} = 0.3$; $K_S = 4.07 \cdot 10^{10} N/m^2$ and $\rho_{sol} = 4 \cdot 10^3 kg/m^3$; $K_B = (1 - \beta)^{3.5} K_S$ and $N = (3/4)K_B$; $\alpha = 2 - \beta$. Here the parameters of bulk He II are used for numerical estimations.















