A Ball in a Groove

Thomas C. Halsey and Deniz Ertaş

Exxon Research and Engineering, Route 22 East, Annandale, N.J. 08801

(May 9, 2018)

We study the static equilibrium of an elastic sphere held in a rigid groove by gravity and frictional contacts, as determined by contact mechanics. As a function of the opening angle of the groove and the tilt of the groove with respect to the vertical, we identify two regimes of static equilibrium for the ball. In the first of these, at large opening angle or low tilt, the ball rolls at both contacts as it is loaded. This is an analog of the "elastic" regime in the mechanics of granular media. At smaller opening angles or larger tilts, the ball rolls at one contact and slides at the other as it is loaded, analogously with the "plastic" regime in the mechanics of granular media. In the elastic regime, the stress indeterminacy is resolved by the underlying kinetics of the ball response to loading.

46.55.+d, 45.70.Cc, 46.25.-y

The behavior of granular materials is one of the most difficult subjects in solid mechanics [1]. It is elementary to state the problem–given a packing of elastic bodies, whose contacts with one another obey the classical Amonton's laws of friction, what is the nature of the stress transmission in the system in the limit where the forces between the bodies are much smaller than the appropriately dimensioned elastic moduli of the bodies? This problem underlies much of soil mechanics, sedimentology, and powder technology, but has thus far resisted *a priori* solution, although much is known at an empirical level about the behavior of such systems [2].

The difficulty of this problem arises from its nonlinearity, which appears in two different guises. In the first place, the forces between elastic bodies in contact are non-linear functions of their displacements. In the second case, sufficiently strong shear forces can cause a contact to fail, which is also a source of non-linearity.

Soil mechanicists often focus on the second source of non-linearity, but presume that at a macroscopic level the first source can be finessed. The result is a class of "elasto-plastic" models that focus on the interplay between an assumed linear elastic region of soil response and the plasticity connected with shear-induced failure [2,3]. While this is a plausible and effective approach, it is disturbing to realize that there is no fundamental reason to expect linear elastic behavior in a granular system at all, given the non-linearity of contact mechanics. This uncertainty in the fundamental underpinnings of granular statics is sometimes termed the "stress indeterminacy" problem, as the stress tensor cannot be determined from the equations of force balance alone; these must be supplemented with some constitutive relations [4].

This uncertainty has motivated statistical approaches to the problem, notably the "q-model" and its variants, which focus on the fluctuations of forces within a granular packing [5]. Unfortunately, these models are not based on a realistic picture of the contact forces between particles.

For this reason, we here address a simple model system, which nevertheless exhibits stress indeterminacy: a



FIG. 1. A ball in a groove is subject to five forces—the gravitational force, which acts on its center of mass, and tangential and normal forces at each contact. The two rigid planes are inclined at angles $\theta_{\left(\frac{L}{R}\right)}$ to the horizontal.

ball placed in a groove with perfectly rigid walls (Figure 1) under gravitational loading. Since the contact mechanics of this system are tractable, we are able to solve its stress indeterminacy problem. We find that it is possible to specify an "elastic" and a "plastic" regime in the behavior of this ball, although the elastic regime is not closely related to ordinary continuum elasticity. In the elastic regime, the stress indeterminacy is lifted by the underlying kinetics of the ball as it is loaded-since the number of kinematic parameters in this case is identical to the number of constraints on the ball, we term this the *isokinetic* regime, in contrast to the *isostatic* plastic regime [6], in which the number of independent forces equals the number of constraints.

Suppose that, as in Fig. 1, we have an elastic sphere of radius R, Young's modulus E, Poisson ratio ν , and mass M in contact with a rigid groove. We consider only motions in the plane perpendicular to the groove axis (out of the page in Fig. 1), thus reducing our problem to an essentially two dimensional one (note however, that we still consider an elastic sphere—the contact mechanics of a disk are essentially different.) θ_L and θ_R denote the angle between the left and right walls of the groove with respect to the horizontal, respectively. Without loss of generality we choose $\theta_L \geq \theta_R$. It is convenient to define $\gamma = \frac{1}{2}(\theta_L + \theta_R)$ and $\delta = \frac{1}{2}(\theta_L - \theta_R)$, so that $\pi - 2\gamma$ is the groove opening angle, and δ gives the tilt of the groove with respect to the vertical. Our definition of a groove satisfies $0 \leq \delta \leq \gamma \leq \frac{\pi}{2}$. The normal and tangential forces exerted by the wall upon the ball are N_L , T_L on the left, and N_R , T_R on the right, with the tangential forces defined so that a force exerted upwards is positive. The ball is also subject to the gravitational force Mg.

$$T_L \sin \theta_L + N_L \cos \theta_L + T_R \sin \theta_R + N_R \cos \theta_R = Mg, \quad (1)$$

$$-T_L \cos \theta_L + N_L \sin \theta_L + T_R \cos \theta_R - N_R \sin \theta_R = 0, \quad (2)$$

$$T_L = T_R, \quad (3)$$

corresponding to the requirements that the net horizontal and vertical forces, and the net torque, be zero. In addition, Amonton's law requires that

$$T_{\binom{L}{R}} \le k N_{\binom{L}{R}},\tag{4}$$

where k is the coefficient of friction between the ball and the wall. Since we have three constraints for the four forces T_L , N_L , T_R , and N_R , even subject to the Amonton's law inequalities we will have in general a manifold of solutions. In order to determine which solution on this manifold is actually chosen we must examine in more detail the mechanics of the ball itself.

The problem of an elastic sphere compressed against a rigid flat surface was given its classical solution by Hertz [7]. If the sphere (of radius R) is loaded by a force normal to the wall N, then its center will displace towards the wall by a distance u, forming thereby a contact circle of radius a, with

$$a = (GNR)^{\frac{1}{3}},\tag{5}$$

$$u = \left(\frac{GN}{\sqrt{R}}\right)^{\frac{4}{3}},\tag{6}$$

where $G = 3(1 - \nu^2)/(4E)$.

The situation in the presence of tangential forces is considerably more complicated [7]. If an already established normal contact is sheared at a tangential force that is insufficient to cause failure, a region of microslip adjacent to the outer perimeter of the contact forms, moving inwards as the tangential force increases. In this region, the two surfaces slip with respect to one another. In the interior of the contact, the two surfaces remain stuck together as the tangential force is applied. Eventually, at failure, there is no stick region left.

The details of this process were explored in a classic paper by Mindlin and Deresiewicz [8]. They observed that the analysis of the contact structure at finite tangential and normal force is only tractable in the limit of low Poisson ratio ν . In this limit the local normal and tangential strains at the contact decouple from one another, so that the normal pressures at the contact are always those of a Hertzian contact with the same overall normal force. Thus the additional tangential strains do not alter the solution of the part of the problem corresponding to the normal force.

The problem is essentially hysteretic, in that the strains corresponding to a given tangential and normal force are determined by the specific history of contact loading leading to these forces. A general increment of force in such a loading history can be described by the change in tangential force δT and the change in normal force δN . A special class of such increments do not involve microslip over some area of the contact surface, those with [8]

$$\delta N > 0, \tag{7}$$

$$|\delta T| < k \delta N. \tag{8}$$

This latter result suggests that we specify a particularly simple loading history of a contact, in which T/Nis maintained constant, with an absolute value $\leq k$, while one force, say N, is monotonically (and adiabatically) increased as a function of time. This type of loading history we term *proportional loading*.

For proportional loading, we can also specify the compliance of the contact, or the values of u_n , u_t , which are respectively the normal and tangential displacements of the center of the ball corresponding to fixed forces N and T. From the Mindlin-Deresiewicz results, it is straightforward to show that for small Poisson ratio,

$$\frac{u_t}{u_n} = \frac{T}{N},\tag{9}$$

with u_n given by the Hertzian result, Eq. (6).

There are other types of motions possible for a contact. One is torsional motion, corresponding to the rotation of the ball about an axis normal to the plane of the contact. Torsional motion leads to couples that vanish as the contact size goes to zero, so we will disregard this type of motion. Rotation of the particle about an axis parallel to the plane of the contact, on the other hand, leads to a rolling motion, in which the center of the contact moves parallel to the underlying plane.

Unfortunately, the strains corresponding to rolling motion have not been successfully computed analytically, even for small Poisson ratio, although a number of approximate solutions have been proposed. For rolling at fixed normal force, there is always a region of microslip at the trailing edge of the contact [7]. However, it does not necessarily follow that a contact that rolls while being proportionally loaded experiences microslip, since the normal force will be increasing in this case. In any case, proportional loading will lead to a unique relation between u_t/u_n and T/N, where u_t is defined as the transverse displacement of the ball center of mass with respect to the contact, not with respect to its initial position. For our purposes, it will be sufficient to use Eq. (9) as an approximate form, since the qualitative properties of the solution are relatively independent of the exact form of the compliance.

In order to insure that the contacts are proportionally loaded, we consider the following experiment. First the ball is placed into the groove at zero gravity so that it barely touches both walls of the groove. Then the gravitational constant is slowly increased from zero to its physical value. Since the external force during this loading increases and does not change direction, we expect $T \propto N$ at each contact with N monotonically increasing.

Let us suppose that the center of mass of the ball moves a distance Z along a path that makes an angle β_L with the left-hand wall and β_R with the right-hand wall (Note that $\beta_L + \beta_R = \pi - 2\gamma$.) During the loading, the ball may also rotate as a rigid body by an angle ϕ , with $\phi > 0$ denoting counterclockwise rolling. Finally, the position of the contacts with the wall will in general move by $u_{c;(\frac{L}{R})}$ on the left and right-hand walls respectively; $u_c > 0$ corresponds to contact motion down the wall.

Now we must specify the normal and tangential displacements of the center of mass of the ball with respect to the contact positions on the two walls. The normal displacements $u_{n:\binom{L}{p}}$ are relatively simple to write:

$$u_{n;\binom{L}{R}} = Z \sin \beta_{\binom{L}{R}}.$$
(10)

The tangential displacements are a little bit more complicated, because of rolling, and because the left and right-hand contacts may have slipped by $d_{\binom{L}{R}}$ during the loading, respectively. Then, $u_{c;L} = -Zv + d_L$ and $u_{c;R} = Zv + d_R$, where $v \equiv R\phi/Z$. Thus, the tangential displacements $u_{t;\binom{L}{R}}$ are given by

$$u_{t;\binom{L}{R}} = Z(\cos\beta_{\binom{L}{R}} \pm v) - d_{\binom{L}{R}}.$$
 (11)

We are now using the five kinematic variables Z, β_L , v, and $d_{\binom{L}{R}}$. The proportional loading assumption insures that whether the contacts are loaded with or without rolling, the forces still obey

$$\frac{u_{t;\binom{L}{R}}}{u_{n;\binom{L}{R}}} = \frac{T}{N},\tag{12}$$

where Amonton's law insures that this is true for sliding contacts as well.

Rolling solutions We first consider solutions in which both contacts roll without sliding: One of the contact points retrogrades up its contact plane, while the other rolls down its plane. Thus we have Eqs. (10) for the normal displacements, while Eqs. (11) become

$$u_{t;\binom{L}{R}} = Z(\cos\beta_{\binom{L}{R}} \pm \upsilon), \tag{13}$$

In principle, we have a uniquely soluble system, since we have the three variables Z, β_L and v describing the kinematics, with three conditions of static equilibrium. However, we must also impose Eqs. (4) constraining the values of T/N. Thus there will be some restricted region of the $\gamma - \delta$ plane in which solution of the Eqs. (1-3) is possible. Substituting Eqs. (10) and (13) into Eqs. (1-3), we obtain

$$\left(\frac{\sin\beta_R}{\sin\beta_L}\right)^{\frac{3}{2}} = \frac{\sin\theta_L}{\sin\theta_R} + \frac{(\cos\beta_L + \upsilon)(\cos\theta_R - \cos\theta_L)}{\sin\beta_L\sin\theta_R},$$
(14)

and

$$\left(\frac{\sin\beta_R}{\sin\beta_L}\right)^{\frac{1}{2}} = \frac{\cos\beta_L + \upsilon}{\cos\beta_R - \upsilon}.$$
(15)

It is straightforward to solve these equations for β_L (and thus β_R) and for v. For $\theta_L = \theta_R$ (or $\delta = 0$), $\beta_L = \beta_R = \frac{\pi}{2} - \gamma$ and v = 0, i.e., there is no rolling and both contacts are stuck. Furthermore,

$$\frac{u_{t;L}}{u_{n;L}} = \frac{u_{t;R}}{u_{n;R}} = \cot \beta_L = \tan \gamma = \frac{T_L}{N_L} = \frac{T_R}{N_R} < k.$$
(16)

Hence, the solution for $\delta = 0$ can only exist for $\gamma < \arctan(k)$, because for $\gamma > \arctan(k)$, the values of T/N corresponding to this solution exceed k. Thus, emanating from the point $(\gamma, \delta) = (\arctan(k), 0)$ is a boundary beyond which double rolling is impossible, because it would require illegal values of T/N > k. This bound is exceeded first on the steeper of the two walls. This boundary, shown as a solid line in Fig. 2, rejoins the γ -axis at $\gamma = 0$, asymptotically merging with the line $\delta = \gamma$.

There is an additional solution for which v = 0 (no rolling), with $\beta_L \neq \beta_R$, that exists for $\frac{\pi}{4} \leq \gamma \leq \arctan(\sqrt{2})$. This additional solution always has at least one of the ratios $T/N \geq \sqrt{2}$, so it can only appear for $k > \sqrt{2}$, and constitutes a boundary between a regime in which the ball rolls clockwise (i.e., down the steeper surface) for smaller γ , and a regime in which the ball rolls counter-clockwise (i.e., up the steeper surface) for larger γ . The values of (γ, δ) for which this solution occurs is shown for k = 10 as a dot-dashed line in Fig. 2.

Rolling-sliding solutions Beyond the boundary at which the steeper wall has T = kN, the only solutions possible are "rolling-sliding" solutions, in which one contact rolls without sliding while the other slides. Assuming that the left-hand wall slides, we have

$$\frac{T_L}{N_L} = k. \tag{17}$$

The equations of static equilibrium then imply

$$\frac{T}{N_R} = \frac{\sin \theta_R}{\cos \theta_R - \cos \theta_L + \frac{1}{k} \sin \theta_L} \equiv \mu,$$
(18)



FIG. 2. Boundaries between different regimes of behavior for coefficient of friction k = 1 (thin lines) and k = 10 (thick lines), as a function of $\gamma = \frac{1}{2}(\theta_L + \theta_R)$ and $\delta = \frac{1}{2}(\theta_L - \theta_R)$. Solid lines mark the boundary between the elastic double-rolling regime below and the plastic rolling-sliding regime above. The dashed and dot-dashed lines mark the boundaries between clockwise (low- γ) and counter-clockwise (high- γ) rolling.

where μ depends only upon the geometry and upon the coefficient of friction k. Note that for $\theta_R < \theta_L$, $\mu < k$, while for $\theta_R > \theta_L$, $\mu > k$. Thus, sliding always occurs on the steeper wall, which is indeed the left-hand wall for $\delta \geq 0$. This is the simplest continuation of the double-rolling solution, which failed at the boundary through incipient sliding at the steeper wall. We have

$$\frac{N_L}{N_R} = \left(\frac{\sin\beta_L}{\sin\beta_R}\right)^{\frac{3}{2}} = \frac{\mu}{k},\tag{19}$$

which can be uniquely solved for β_L and β_R . In addition, the criterion that the ball rolls at the right-hand contact implies that

$$\frac{T}{N_R} = \mu = \frac{\cos\beta_R - \upsilon}{\sin\beta_R},\tag{20}$$

which allows us to solve for $v(\beta_R)$.

The physical constraint $d_L > 0$ sets the boundary on the region with a rolling-sliding solution, which, for $\gamma < \arctan(k)$, coincides with the upper boundary of the double rolling solution discussed in the previous section. For $\delta = 0$ we have v = 0 and $T/N_R = k$, and this solution collapses onto a double sliding solution for $\gamma > \arctan(k)$. In addition, there is a line of solutions with v = 0, corresponding to one contact sliding and the other being stuck. For $k < \sqrt{2}$ this line emanates from $(\gamma, \delta) = (\arctan(k), 0)$ and ends at $(\gamma, \delta) = (\frac{\pi}{4}, \frac{\pi}{4})$. For $k > \sqrt{2}$, this line emanates from the point on the boundary of the double rolling region for which v = 0, and ends at $(\gamma, \delta) = (\frac{\pi}{4}, \frac{\pi}{4})$ (dashed lines in Fig. 2). As for the double rolling v = 0 line, this line separates the low- γ clockwise rolling from the high- γ counterclockwise rolling.

Much discussion of the statics of granular media has emphasized the two limits of plastic and linear elastic behavior. Clearly the rolling-sliding regime of the ball in the groove is a good analog to plastic behavior—in this regime, the problem is *isostatic*, meaning that the number of independent forces is identical to the number of constraints. In the double rolling regime, the state of the ball is specified by its displacements, as in conventional elasticity theory. However, minimization of the strain energies corresponding to the contact forces plays no role in resolving the stress indeterminacy.

It is instructive to consider the relationship between the forces and the underlying degrees of freedom Z, β_L , v, and $d_{\binom{L}{R}}$. The four forces $T_{\binom{L}{R}}$ and $N_{\binom{L}{R}}$ are functions of these five underlying variables. In the double-rolling regime, $d_{\binom{L}{R}} = 0$, and there are only three active variables, which are then uniquely fixed by the equations of static equilibrium. We call this an isokinetic configuration, because the number of kinetic degrees of freedom equals the number of constraints enforcing equilibrium.

On the other hand, as one passes into the isostatic rolling-sliding regime, one acquires a new degree of freedom d_L , so that there are now four underlying active degrees of freedom. However, one of these degrees of freedom is used to fix $T_L = kN_L$, so in practice there are three degrees of freedom remaining to satisfy the equations of static equilibrium.

We are grateful to P.M. Chaikin and D. Levine for stimulating discussions.

- H. M. Jaeger, S. R. Nagel, and R. P. Behringer, Rev. Mod. Phys. 68, 1259 (1996).
- [2] R. M. Nedderman, Statics and Kinematics of Granular Materials (Cambridge U. P., New York, 1992) Chapter 3.
- [3] D. M. Wood, Soil Behaviour and Critical State Soil Mechanics (Cambridge U.P., New York, 1990); F. Cantelaube and J.D. Goddard, in *Powders and Grains 97*, eds. R.P. Behringer and J.T. Jenkins, (Balkema, Rotterdam, 1997).
- [4] A notable recent approach is found in J.P. Wittmer, M.E. Cates, and P. Claudin, J. Phys. I France 7, 39 (1997).
- [5] S.N. Coppersmith, C.-H. Liu, S. Majumdar, O. Narayan, and T.A. Witten, Phys. Rev. E 53, 4673 (1996); J. Socolar, Phys. Rev. E 57, 3204 (1998).
- [6] C.F. Moukarzel, Phys. Rev. Lett. 81, 1634 (1998).
- [7] K.L. Johnson, *Contact Mechanics* (Cambridge U.P., New York, 1985).
- [8] R.D. Mindlin and H. Deresiewicz, Journal of Appl. Mech., 20, 327 (1953).