# Methods for Computing Normalisations of Affine Rings

A. TAYLOR

Abstract. Our main purpose is to give multiple examples for using the available implementations for computing the normalization of an affine ring, computing the minimial generators of the normalization as an algebra over the original ring and integral closures of ideals. Some such examples have been published for SINGULAR, but not for MACAULAY 2 and we present both in this paper. We also briefly describe the implementations.

#### 1. Introduction

In this note we describe the available methods for computing the normalization of affine rings, that is reduced, finite, k-algebras, where k is a computable field, and the implications for computing the integral closure of ideals. Our goal is to keep it simple. Much more is known for computing the normalization with assumptions on the ring or the ideal, as well as for the normalization of discrete valuation rings. We only address what can be done in the most general setting of affine rings.

Our main goal is to give examples so that users can fully exploit the implementations. We also briefly describe which algorithms have been implemented, some implementation issues and how to use these implementations to compute the integral closure of small ideals. All computations listed in this paper were done on a Pentium III, 600 MHZ machine with 256 MB of RAM.

At the time of this writing there are two implementations of normalization. One implementation is in MACAULAY 2 [5] and the other is in SINGULAR [10]. Both implementations are based on the information given in de Jong's paper [12]. The philosophical approach of which is seen in Vasconcelos' papers [16] and [18] and a more detailed analysis of this approach is given in [2]. A brief description as well as other examples for SINGULAR are given in [8]. Finally, there will be chapter on normalization, computing it in SINGULAR, and related issues in the upcoming book of Greuel and Pfister [9]. All of what is published is based on the implementation in SINGULAR, where as this is the first document detailing what is done in MACAULAY 2 as well.

The research of the author was paritally supported the National Security Agency.

### A. TAYLOR

Let A = R/I be an affine ring. In the following we use the language of Matsumura [13]. If A is a domain and Q its ring of fractions then the *integral closure*  $\overline{A}$  of A is the set of all elements in Q that are integral over A and A is *integrally closed* if  $A = \overline{A}$ . An affine ring A is *normal* if  $A_p$  is an integrally closed domain at every prime  $p \in \text{Spec}(A)$ . If A is normal it is well known that  $A \cong A/P_1 \times \cdots A/P_t$  where  $P_1, \ldots P_t$  are the minimal primes for A and  $A/P_i$  is an integrally closed domain for  $1 \leq i \leq t$ . Since the implementations deal with affine rings in general this decomposition is often referred to as the *normalization* of A rather than the integral closure. MACAULAY 2 refers to the computation as integral closure where as SINGULAR and all of the publications associated to its implementation call the computation normalization. To emphasize that we do not require the ring to be a domain, we also refer to the computation as normalization.

Serre's criterion for normality implies that an affine ring A is normal if and only if it is both  $S_2$  and  $R_1$  [13, Theorem 23.8]. An affine ring is  $S_2$ if  $A_p$  is Cohen-Macaulay for  $p \in \text{Spec}(A)$  and  $\text{codim}(p) \leq 2$ , and has depth greater than or equal to 2 for  $p \in \text{Spec}(A)$  and codim(p) > 2. An affine ring is  $R_1$  if it is regular in codimension one.

The philosophy of the approach is to enlarge A recursively inside of Q until the normalization of A is obtained. The extension Vasconcelos uses in [16], [18] is Hom(Hom(L, A), Hom(L, A)), where L is the Jacobian ideal of A. The following key theorem in de Jong's paper [12] is originally due to Grauert and Remmert [6, pp. 220-221], [7, pp. 125-127] and describes the ring de Jong uses for this extension. The non-normal locus of A is the set  $NNL \subseteq \text{Spec}(A)$  such that for  $p \in NNL$ ,  $A_p$  is not an integrally closed domain.

THEOREM 1.1. Let A = R/I be an affine ring and J an ideal of A. Assume that the ideal J contains a non-zero divisor, and has the following property:

$$NNL \subseteq V(J),$$

where  $V(J) = \{p \in \text{Spec}(A) | J \subset p\}$  denotes, as usual, the zero set of J. Suppose moreover that J has the property

(1.2) 
$$\operatorname{Hom}_A(J,J) = \operatorname{Hom}_A(J,A) \cap A$$

Then one has the following normality criterion:

 $A = \operatorname{Hom}_A(J, J)$  if and only if A is normal.

The implementations in both MACAULAY 2 and SINGULAR are split into two phases. First they find an ideal J such that the non-normal locus of A is contained in V(J) and satisfying Equations (1.2). In the second phase Hom(J, J) is computed as a ring.

For the first phase, Theorem 2.2 in de Jong's paper [12] establishes that any radical ideal containing a non-zero divisor satisfies Equation (1.2). Also, it is well known that if the Jacobian ideal L of A is not contained in  $Q \in \text{Spec}(A)$  then  $A_Q$  is regular, so the non-normal locus of A is contained in  $V(L) = V(\sqrt{L})$ . Hence  $\sqrt{L}$  satisfies Theorem 1.1. Computing L can be very complex in terms of space and time, so sometimes the programs may use  $\sqrt{f}$  for  $f \in L$  non-zero which also satisfies the hypotheses of Theorem 1.1.

For the second phase, there are two facts that are very helpful. The first, is the well known fact that if f is a non-zero divisor in A, then  $(fJ:J) = f\operatorname{Hom}(J,J)$ . The second, is the presentation of  $\operatorname{Hom}(J,J)$  as a ring that is due to Catanese [1] and is given in de Jong's paper [12, Theorem 3.1]. Let  $v_1, \ldots, v_n$  be a module basis for  $\operatorname{Hom}(J,J)$ . Map  $S = k[X_1, \ldots, X_n]$  onto  $\operatorname{Hom}(J,J)$  by sending  $X_i$  to  $v_i$  for  $1 \leq i \leq n$ . Then as a ring  $\operatorname{Hom}(J,J)$  is defined by two sets of relations. There are linear equations which are the syzygies for the module,  $\sum \alpha_i X_i = 0$  and quadratic equations which come from the fact that  $\operatorname{Hom}(J,J)$  is a ring so there exists  $\beta_{ijk}$ ,  $1 \leq k \leq n$  such that  $v_i v_j = \sum \beta_{ijk} v_k$ . It is a theorem of Catanese stated clearly in [2] and [12] that the ideal generated by these two sets of relations is the full kernel of the map, thus inducing an isomorphism.

The implementations in MACAULAY 2 and SINGULAR were completed independently, but the pseudo-code for both is very close to the presentation in [2] so we will not include it here.

The casual user looking at the code in either program will see relatively complicated programs which is due to the recursive nature of the algorithm. The program must track the proper extensions and in the case of reduced rings, it must track the splitting of the ring into domains. Often for an ideal J as in the theorem, while Hom(J, J) is a proper extension, it is not the normalization yet so the process must be repeated many times. It is unknown, given the ring, the number of extensions that must be computed. Moreover, experimental experience suggests that there are choices available that could reduce the number of extensions that need to be computed, but knowing when to use them is not always a priori clear. There is a new algorithm of Vasconcelos' for which the number of recursions is bounded, but this algorithm is not yet implemented in any of the systems [17].

# 2. Examples

For the examples we will focus on a hypersurface given to us by Craig Huneke, a union of straight lines given in the SINGULAR example files and an example of Huneke's given in each of [2], [15], [16], and [18]. Also the first and third examples were chosen because one satisfies Serre's condition  $S_2$  but does not satisfy Serre's condition  $R_1$  and the other is the opposite.

For each of the examples we give the input and output of both programs so that the user can simply type in the same information and see the same results. Occasionally, due to the width of the text we have had to slightly alter the output for it to fit in the space allotted. We hope that this is also enough information for the user to then perform similar computations on their own examples. Also, when possible we include the computation times in CPU seconds. If no time is listed it is because the time is negligible. We include the times because they are indicative of what can happen on larger examples and because they give more meaning to the times listed after Example 2.6. However, when taken by themselves the times may not have much meaning since even on the same machine times can vary up to a few seconds. EXAMPLE 2.1. Let  $A = \mathbb{Q}[x, y, z]/(x^6 - z^6 - y^2 z^4)$ . This ring is not R1, but it is S2. Therefore, computing the normalization in the example forms the desingularization of A in codimension one. The computation in MACAULAY 2 follows.

i1 :  $A = QQ[x,y,z]/ideal(x^6-z^6-y^2*z^4)$ 

o1 = A

- o1 : QuotientRing
- i2 : time integralClosure (A, Variable => symbol a)
   -- used 1.67 seconds



### o2 : QuotientRing

Computing the normalization of an affine ring requires new variables unless the ring is already normal. MACAULAY 2 gives the user the opportunity to specify which letter to use for this new variable. This is done via

Variable => symbol a.

If this is not included, then MACAULAY 2 uses w by default. Using a letter to create the normalization which is a variable in the definition of R can lead to problems with using the normalization, so we recommend supplying a variable not used to define R.

For SINGULAR, we must first load the normalization library. SINGULAR then lists the libraries loaded and we use elipses to indicate that more is printed on that line, but we have removed it to keep from having to make multiple lines due to the size of the paper. Also, we use nor to name the output of normal(I) to match the comments that singular outputs as part of this function. We then follow the other commands they list for continuity.

```
> LIB "normal.lib";
```

```
// ** loaded /usr/local/Singular/2-0-3/LIB/normal.lib ...
```

```
// ** loaded /usr/local/Singular/2-0-3/LIB/hnoether.lib ...
```

```
// ** loaded /usr/local/Singular/2-0-3/LIB/primitiv.lib ...
```

```
// ** loaded /usr/local/Singular/2-0-3/LIB/random.lib ...
```

```
// ** loaded /usr/local/Singular/2-0-3/LIB/matrix.lib ...
```

```
// ** loaded /usr/local/Singular/2-0-3/LIB/ring.lib ...
```

```
// ** loaded /usr/local/Singular/2-0-3/LIB/inout.lib ...
```

```
// ** loaded /usr/local/Singular/2-0-3/LIB/presolve.lib ...
```

```
// ** loaded /usr/local/Singular/2-0-3/LIB/elim.lib ...
```

```
// ** loaded /usr/local/Singular/2-0-3/LIB/primdec.lib ...
```

```
4
```

```
// ** loaded /usr/local/Singular/2-0-3/LIB/sing.lib ...
// ** loaded /usr/local/Singular/2-0-3/LIB/poly.lib ...
// ** loaded /usr/local/Singular/2-0-3/LIB/general.lib ...
> ring R = 0, (x, y, z), dp;
> ideal I= x6-z6-y2z4;
> list nor = normal(I);
// 'normal' created a list of 1 ring(s).
// nor[1+1] is the delta-invariant in case of choose=wd.
// To see the rings, type (if the name of your list is nor):
     show( nor);
// To access the 1-st ring and map (similar for the others),
     type: def R = nor[1]; setring R; norid; normap;
// R/norid is the 1-st ring of the normalization and
// normap the map from the original basering to R/norid
> timer=1;
//used time: 0.82 sec
> show(nor);
// list, 1 element(s):
[1]:
   // ring: (0),(T(1),T(2),T(3),T(4),T(5)),
                           (a(1,1,1,1,1),dp(5),C);
   // minpoly=0
// objects belonging to this ring:
// normap
                        [0] ideal, 3 generator(s)
// norid
                        [0] ideal, 4 generator(s)
> setring S; norid;
norid[1]=T(4)^2-T(1)*T(5)
norid[2]=T(1)*T(4)-T(3)*T(5)
norid[3]=T(2)^2+T(3)^2-T(5)^2
norid[4]=T(1)^2-T(3)*T(4)
```

The the output of the command show(nor); states that the normalization of R/I requires only one ring because R/I was a domain. If we denote the normalization of R/I by S/L then the next line tells us that  $S = \mathbb{Q}[T(1), T(2), T(3), T(4), T(5)]$ , each variable has degree 1 and the ordering is degree reverse lexicographic. The next two lines tell us that in SINGULAR there are two other objects assigned to this ring. The first defines the natural map from R/I into S/L and the second is the the defining ideal L of the integral closure. To see generators of L we execute the two commands setring S; and norid;.

The information stored in the outputs of the two programs is fundamentally the same, but the presentation of the output in the two programs is a little different. MACAULAY 2 preserves the fact that  $A \subset \text{Hom}(J, J)$  and thus computes a presentation that includes those variables from A which still contribute to a minimal presentation. In contrast, SINGULAR uses all new variables and in this example T(1) = x, T(2) = y, T(3) = z, T(4) = $a_6, T(5) = a_7$ . The fractions computed in Example 2.4 can be used to find this correspondence. MACAULAY 2 allows the user to choose the name of the new variables, but SINGULAR does not have such an option. When SIN-GULAR computes normal(I) it gives information about the number of rings in the decomposition and stores this information in the list we called nor above and then a few commands are used to display this information. In this example there is one ring, but in the next example when the input is not a domain we are told there are 3 rings, so we do the display information three times. In MACAULAY 2 for a domain, the domain that is the normalization is displayed unless we suppress it using a semicolon. When the ring is not a domain, a sequence of normal rings, such that the direct sum of these rings is the normalization of the reduced ring is displayed.

EXAMPLE 2.2. Let A be a union of lines,  $A = \mathbb{Q}[x, y, z]/((x - y)(x - z)(y - z))$ . i1 : A = QQ[x,y,z]/ideal((x-y)\*(x-z)\*(y-z))

i2 : time integralClosure(A,Variable => V)
 -- used 0.47 seconds

$$QQ [V, y, z] 0 R02 = (------, -----)2 y - zV + V0 0$$

#### o2 : Sequence

Before proceeding to the SINGULAR example we consider the presentation of the first ring. The output of MACAULAY 2 will always give a normal ring, but not necessarily a domain. Here it gives

$$\frac{\mathbb{Q}[V_0, y, z]}{V_0^2 + V_0} \cong \frac{\mathbb{Q}[V_0, y, z]}{V_0 + 1} \oplus \frac{\mathbb{Q}[V_0, y, z]}{V_0}$$

which is normal. In contrast, MACAULAY 2 computes the normalization of  $\mathbb{Q}[V_0, y, z]/(V_0^2 + V_0)$  as the isomorphic presentation.

Using SINGULAR, the output of normal(I) reveals that there are three rings. What follows reveals that each of the three rings is isomorphic to  $\mathbb{Q}[x, y]$ . This is the information we gained from MACAULAY 2 in an isomorphic format. Since we ran this example in the same session as the previous example, we do not need

```
> LIB "normal.lib";
```

this time. However, if the SINGULAR session is restarted then this command is needed to get the same results.

```
> ring R=0,(x,y,z),dp; ideal I=(x-y)*(x-z)*(y-z);
> list nor=normal(I);
```

```
// 'normal' created a list of 3 ring(s).
// nor[3+1] is the delta-invariant in case of choose=wd.
```

```
// To see the rings, type (if the name of your list is nor):
     show( nor);
// To access the 1-st ring and map (similar for the others),
     type: def R = nor[1]; setring R; norid; normap;
// R/norid is the 1-st ring of the normalization and
// normap the map from the original basering to R/norid
> timer=1;
> show(nor);
// list, 3 element(s):
[1]:
   //ring: (0),(T(1),T(2)),(dp(2),C);
   // minpoly = 0
// objects belonging to this ring:
                        [0] ideal, 3 generator(s)
// normap
// norid
                        [0]
                             ideal, 1 generator(s)
[1]:
   //ring: (0),(T(1),T(2)),(dp(2),C);
   // minpoly = 0
// objects belonging to this ring:
// normap
                        [0] ideal, 3 generator(s)
// norid
                        [0] ideal, 1 generator(s)
[1]:
   //ring: (0),(T(1),T(2)),(dp(2),C);
   // minpoly = 0
// objects belonging to this ring:
// normap
                        [0] ideal, 3 generator(s)
                        [0] ideal, 1 generator(s)
// norid
> def S1=nor[1]; def S2=nor[2]; def S3=nor[3];
> setring S1; norid; setring S2; norid; setring S3; norid;
norid[1]=0
norid[1]=0
norid[1]=0
Since there are three rings whose direct sum forms the normalization of
```

Since there are three rings anose affect sum joints the normalization of A = R/I the output of show(nor); gives the defining rings for all three and we see they are the same. Then we ask for the defining ideal and get that it is zero, so

 $\overline{A} \cong \mathbb{Q}[T(1), T(2)] \oplus \mathbb{Q}[T(1), T(2)] \oplus \mathbb{Q}[T(1), T(2)]$ 

which is essentially the same information we got from MACAULAY 2.

EXAMPLE 2.3. This example was chosen to because this ring has an isolated singularity, so it is  $R_1$ , but is not  $S_2$  in contrast to the first example. Thus the normalization of this ring is its  $S_2$ -ification. This example also takes a little longer than the previous examples. Let I be the radical of the ideal generated by

$$ab^{3}c + bc^{3}d + a^{3}be + cd^{3}e + ade^{3},$$
  
$$a^{2}bc^{2} + b^{2}cd^{2} + a^{2}d^{2}e + ab^{2}e^{2} + c^{2}de^{2},$$
  
$$a^{5} + b^{5} + c^{5} + d^{5} - 5abcde + e^{5}$$

 $\overline{7}$ 

We use a few new commands in MACAULAY 2 this time to make the output more presentable for this paper, however these are not needed when a user runs MACAULAY 2 in emacs since the output is reasonable with wrap-around turned off. Even with these new commands we altered the presentation of the output a little for both programs to make them more readable in this paper.

```
i1 : R = QQ[a..e];
i2 : time I = radical(ideal(
a*b^3*c+b*c^3*d+a^3*b*e+c*d^3*e+a*d*e^3,
a<sup>2</sup>*b*c<sup>2</sup>+b<sup>2</sup>*c*d<sup>2</sup>+a<sup>2</sup>*d<sup>2</sup>*e+a*b<sup>2</sup>*e<sup>2</sup>+c<sup>2</sup>*d*e<sup>2</sup>,
a<sup>5+b</sup>5+c<sup>5+d</sup>5-5*a*b*c*d*e+e<sup>5</sup>);
      -- used 5.77 seconds
i3 : time V = integralClosure (R/I, Variable => X);
      -- used 4.23 seconds
i4 : ring ideal V
o4 = QQ [X ,X ,a,b,c,d,e, Degrees =>
             0 1
                                        \{\{5\},\{5\},\{1\},\{1\},\{1\},\{1\},\{1\}\}\}
o4 : PolynomialRing
i5 : toString ideal V
o5 = ideal(a^2*b*c^2+b^2*c*d^2+a^2*d^2*e+a*b^2*e^2+c^2*d*e^2,
a*b^3*c+b*c^3*d+a^3*b*e+c*d^3*e+a*d*e^3,
a<sup>5+b</sup>5+c<sup>5+d</sup>5-5*a*b*c*d*e+e<sup>5</sup>,
a*b*c^4-b^4*c*d-X_0*e-a^2*b^2*d*e+a*c^2*d^2*e+b^2*c^2*e^2
         -b*d^2*e^3,
a*b^2*c^3+X_1*d+a*b*c*d^2*e-a^2*b*e^3-d*e^5,
a<sup>3</sup>*b<sup>2</sup>*c-b*c<sup>2</sup>*d<sup>3</sup>-X_1*e-b<sup>5</sup>*e-d<sup>5</sup>*e+2*a*b*c*d*e<sup>2</sup>,
a<sup>4</sup>*b*c+X_0*d-a*b<sup>4</sup>*e-2*b<sup>2</sup>*c<sup>2</sup>*d*e+a<sup>2</sup>*c*d*e<sup>2</sup>+b*d<sup>3</sup>*e<sup>2</sup>,
X_1*c+b^5*c+a^2*b^3*e-a*b*c^2*d*e-a*d^3*e^2,
X_0*c-a^2*b^2*c*d-b^2*c^3*e-a^4*d*e+2*b*c*d^2*e^2+a*b*e^4,
X_1*b-b*c^5+2*a*b^2*c*d*e-c^3*d^2*e+a^3*d*e^2-b*e^5,
X_0*b+a*b*c<sup>2</sup>*d<sup>2</sup>-b<sup>3</sup>*c<sup>2</sup>*e+a*d<sup>4</sup>*e-a<sup>2</sup>*b*c*e<sup>2</sup>+b<sup>2</sup>*d<sup>2</sup>*e<sup>2</sup>
      -c*d*e^4.
X_1*a-b^3*c^2*d+c*d^2*e^3,
X_0*a-b*c*d^4+c^4*d*e,
X_1^2+b^5*c^5+b^4*c^3*d^2*e+b*c^2*d^3*e^4+b^5*e^5+d^5*e^5,
X_0*X_1+b^3*c^4*d^3-b^2*c^7*e+b^2*c^2*d^5*e-b*c^5*d^2*e^2
         -a*b^2*c*d^3*e^3+b^4*c*d*e^4+a^2*b^2*d*e^5
         -a*c^2*d^2*e^5-b^2*c^2*e^6+b*d^2*e^7,
X_0^2+b*c^3*d^6+2*b^5*c*d^3*e+c*d^8*e-b^4*c^4*e^2
      +a^3*c^3*d^2*e^2+2*a^2*b^3*d^3*e^2-5*a*b*c^2*d^4*e^2
      +4*b^3*c^2*d^2*e^3-3*a*d^6*e^3+5*a^2*b*c*d^2*e^4
      -b^2*d^4*e^4-2*b*c^3*d*e^5-a^3*b*e^6+3*c*d^3*e^6-a*d*e^8)
```

8

The command "ring ideal V" gives the polynomial ring and "toString ideal V" gives the defining ideal for the normalization.

In MACAULAY 2 we computed the radical of the three equations and then computed the normalization. SINGULAR and MACAULAY 2 use different algorithms for the command radical which means that there are examples which run well in one program, but not the other. The radical computation done above in MACAULAY 2 does not finish in SINGULAR on the Pentium III, 600 MHZ machine with 256 MB of RAM, but this is a feature of this example. We could just as easily find an example that SINGULAR completes and MACAULAY 2 does not. In SINGULAR we ran the normalization computation on the radical obtained from MACAULAY 2. Also this time we do not do the command show(nor); because the output is similar to that of the first example. Finally, as we did above, we alter the output a little to make it more readable for this paper.

```
> ring R = 0, (a,b,c,d,e), dp;
> ideal I = a2bc2+b2cd2+a2d2e+ab2e2+c2de2,
ab3c+bc3d+a3be+cd3e+ade3,
a5+b5+c5+d5-5abcde+e5,
a3b2cd-bc2d4+ab2c3e-b5de-d6e+3abcd2e2-a2be4-de6,
abc5-b4c2d-2a2b2cde+ac3d2e-a4de2+bcd2e3+abe5,
ab2c4-b5cd-a2b3de+2abc2d2e+ad4e2-a2bce3-cde5,
b6c+bc6+a2b4e-3ab2c2de+c4d2e-a3cde2-abd3e2+bce5,
a4b2c-abc2d3-ab5e-b3c2de-ad5e+2a2bcde2+cd2e4;
list nor = normal(I);
// 'normal' created a list of 1 ring(s).
// nor[1+1] is the delta-invariant in case of choose=wd.
// To see the rings, type (if the name of your list is nor):
     show( nor);
// To access the 1-st ring and map (similar for the others),
     type: def R = nor[1]; setring R; norid; normap;
// R/norid is the 1-st ring of the normalization and
// normap the map from the original basering to R/norid
> timer=1;
//used time: 3.21 sec
> def S = nor[1]; setring S; norid;
norid[1]=T(1)^2*T(2)*T(3)^2+T(2)^2*T(3)*T(4)^2
        +T(1)^2*T(4)^2*T(5)+T(1)*T(2)^2*T(5)^2
        +T(3)^2*T(4)*T(5)^2
norid[2]=T(1)*T(2)^3*T(3)+T(2)*T(3)^3*T(4)+T(1)^3*T(2)*T(5)
        +T(3)*T(4)^{3}T(5)+T(1)*T(4)*T(5)^{3}
norid[3]=T(1)^5+T(2)^5+T(3)^5+T(4)^5
        -5*T(1)*T(2)*T(3)*T(4)*T(5)+T(5)^5
norid[4]=T(2)*T(3)*T(4)^4-T(3)^4*T(4)*T(5)-T(1)*T(6)
norid[5]=T(1)*T(2)*T(3)^2*T(4)^2-T(2)^3*T(3)^2*T(5)
        +T(1)*T(4)^{4}T(5)-T(1)^{2}T(2)*T(3)*T(5)^{2}
        +T(2)^{2}T(4)^{2}T(5)^{2}-T(3)*T(4)*T(5)^{4}+T(2)*T(6)
norid[6]=T(2)^3*T(3)^2*T(4)-T(3)*T(4)^2*T(5)^3-T(1)*T(7)
```

```
norid[7]=T(1)^2*T(2)^2*T(3)*T(4)+T(2)^2*T(3)^3*T(5)
+T(1)^{4}T(4)*T(5)
        -2*T(2)*T(3)*T(4)^2*T(5)^2-T(1)*T(2)*T(5)^4-T(3)*T(6)
norid[8]=T(2)*T(3)^5-2*T(1)*T(2)^2*T(3)*T(4)*T(5)
+T(3)^{3}T(4)^{2}T(5)
        -T(1)^{3}T(4)T(5)^{2}T(2)T(5)^{5}T(2)T(7)
norid[9]=T(1)*T(2)*T(3)^4-T(2)^4*T(3)*T(4)
        -T(1)^{2}T(2)^{2}T(4)T(5)+T(1)T(3)^{2}T(4)^{2}T(5)
        +T(2)^2*T(3)^2*T(5)^2-T(2)*T(4)^2*T(5)^3-T(5)*T(6)
norid[10]=T(1)*T(2)^2*T(3)^3+T(1)*T(2)*T(3)*T(4)^2*T(5)
         -T(1)^{2}T(2)T(5)^{3}-T(4)T(5)^{5}+T(4)T(7)
norid[11]=T(2)^5*T(3)+T(1)^2*T(2)^3*T(5)
         -T(1)*T(2)*T(3)^{2}*T(4)*T(5)
         -T(1)*T(4)^{3}T(5)^{2}+T(3)*T(7)
norid[12]=T(1)^3*T(2)^2*T(3)-T(2)*T(3)^2*T(4)^3-T(2)^5*T(5)
         -T(4)^{5}T(5)+2T(1)T(2)T(3)T(4)T(5)^{2}-T(5)T(7)
norid[13]=T(1)<sup>4</sup>*T(2)*T(3)-T(1)*T(2)<sup>4</sup>*T(5)
         -2*T(2)^2*T(3)^2*T(4)*T(5)+T(1)^2*T(3)*T(4)*T(5)^2
         +T(2)*T(4)^3*T(5)^2+T(4)*T(6)
norid[14]=T(2)^4*T(3)*T(4)*T(5)^4+2*T(1)^3*T(4)^3*T(5)^4
         +4*T(1)^2*T(2)^2*T(4)*T(5)^5
         -4*T(1)*T(3)^2*T(4)^2*T(5)^5+2*T(2)*T(4)^2*T(5)^7
         +T(1)*T(2)*T(3)*T(4)*T(5)*T(6)
         +T(1)*T(3)^2*T(4)^2*T(7)-T(2)^2*T(3)^2*T(5)*T(7)
         -4*T(1)^2*T(3)*T(5)^2*T(7)-T(2)*T(4)^2*T(5)^2*T(7)
         +T(6)*T(7)
norid[15]=2*T(1)^2*T(2)*T(4)^4*T(5)^3
         -T(1)*T(2)^3*T(4)^2*T(5)^4-T(2)*T(3)^2*T(4)^3*T(5)^4
         +3*T(4)^5*T(5)^5+2*T(1)*T(2)*T(3)*T(4)*T(5)^6
         +3*T(2)^2*T(3)*T(4)^2*T(6)+2*T(1)*T(2)^2*T(5)^2*T(6)
         +2*T(3)^2*T(4)*T(5)^2*T(6)-2*T(3)^5*T(7)
         -3*T(4)^{5*T(7)+3*T(1)*T(2)*T(3)*T(4)*T(5)*T(7)}
         -2*T(5)^{5}T(7)+2*T(7)^{2}
norid[16]=T(1)<sup>3</sup>T(2)T(4)<sup>5</sup>T(5)-T(1)<sup>3</sup>T(3)<sup>3</sup>T(4)<sup>2</sup>T(5)<sup>2</sup>
         -T(2)^{2}T(4)^{4}T(5)^{4}+T(2)*T(3)^{3}T(4)*T(5)^{5}
         +T(1)^2*T(2)^2*T(4)*T(6)+T(2)^2*T(3)^2*T(5)*T(6)
         -2*T(2)*T(4)^2*T(5)^2*T(6)-T(6)^2
```

SINGULAR used approximately 1 CPU second less than MACAULAY 2 for this normalization computation. As examples get larger this could be significant in obtaining success.

There are two other operations we want to illustrate. Assume A = R/I is an affine domain. These first three examples give the integral closure of A in the form S/L where S is of the form  $R[Y_0, \ldots, Y_t]$  and  $S/L \cong \overline{A}$ . If A is a domain a user may want the fractions from the quotient field that generate the normalization of A as a finite algebra over A. This information can be obtained using both MACAULAY 2 and SINGULAR.

EXAMPLE 2.4. For simplicity we use the same hypersurface as Example 2.1.

11

i1 :  $A = QQ[x,y,z]/ideal(x^6-z^6-y^2*z^4);$ 

o2 = | x3/z2 x2/z x y z |

$$1 \qquad 5$$
o2 : Matrix frac A <--- frac A

Thus  $A[x^3/z^2, x^2/z] = A$ .

In SINGULAR the method for obtaining the fractions is considerably different. Several auxiliary functions are used. The library normal.lib is no longer used and instead we need reesclos.lib. SINGULAR is very particular how you define the ideal defining the affine domain. It must be named ker or an error will be issued. The output has the following form.

fraction;
[1]:
 xyz8
[2]:
 yz8

Then the fraction we are looking for is [1] divided by [2], that is  $\frac{xyz^8}{yz^8} = x$ . The fractions found in this way in SUNGULAR are after not reduced.

The fractions found in this way in SINGULAR are often not reduced.

We use a new library in this example and since we included the printed output that is given when a library is loaded into SINGULAR in Example 2.1, we removed it this time.

```
> LIB "reesclos.lib";
> ring R=0,(x,y,z),lp; ideal ker=x6-z6-y2z4;
> list L=primeClosure(R); closureRingtower(L);
> setring R(6); poly f=T(1); closureFrac(L);
> setring R(1); fraction;
[1]:
   xyz8
[2]:
   vz8
> setring R(6); poly f=T(2); closureFrac(L);
> setring R(1); fraction;
// ** redefining f **
[1]:
   y2z8
[2]:
   yz8
> setring R(6); poly f=T(3); closureFrac(L);
> setring R(1); fraction;
// ** redefining f **
[1]:
   yz9
[2]:
```

```
yz8
> setring R(6); poly f=T(4); closureFrac(L);
> setring R(1); fraction;
// ** redefining f **
[1]:
   x2yz7
[2]:
   yz8
> setring R(6); poly f=T(5); closureFrac(L);
> setring R(1); fraction;
// ** redefining f **
[1]:
   x3yz6
[2]:
   yz8
> timer=1;
//used time: 1.66 sec
```

We can use this output from MACAULAY 2 and SINGULAR to find a map from the variables used by Macaulay 2 to those used by Singular and vice versa. Also, given any element of the presentation of  $\overline{A}$  as S/J, SINGULAR can find its image in the ring of fractions of A. This is not currently set up in MACAULAY 2.

Before computing the integral closure of an ideal, we point out one other subtle difference between the two programs. In MACAULAY 2 it is possible to define multigraded rings and the integralClosure program is designed to handle such rings, while in SINGULAR it is not possible to define such rings. Multigraded rings play an important role in computing the integral closure of an ideal in MACAULAY 2. Since it is not possible to define a multigraded ring in SINGULAR the implementation there must be fundamentally different from that in MACAULAY 2.

It is possible, theoretically, to compute the integral closure of an ideal using both systems. We say theoretically because the computation is often much too complex to complete, either due to memory or time (mostly memory). The approach, in both systems, is the classical one, that is compute the Rees algebra first, find the normalization of the Rees algebra and then find the degree one piece of that graded algebra.

In MACAULAY 2 a function to compute  $\overline{I}$  is not yet implemented in the main distribution, but we include one in the appendix which is being submitted to MACAULAY 2 for inclusion. To run this program, a program to compute the Rees algebra that preserves the natural multigrading is needed. We also include the code for this in the appendix. There are several such programs for MACAULAY 2 in circulation. Besides the one in the appendix, one can be found in [14] and we have received yet another via personal communication from David Eisenbud. A package of such programs is being put together for inclusion with MACAULAY 2. The one we include here is the only one that incorporates the natural multigrading, but is otherwise fundamentally the same as that in [14], which could be easily altered to use the grading. The program communicated by David Eisenbud is more general

```
12
```

and is based on his paper with Huneke and Ulrich [3]. Both computing blowups and integral closure of ideals are functions in SINGULAR if the Rees library has been loaded.

We include two complete examples and discuss briefly two others. The first example is one that can be checked by hand using standard techniques. The second example is considerably more complicated and the remaining ideals illustrate how easily this process fails to complete. All the examples are small in the sense that they use at most three generators, use at most three variables and have degree at most seven.

EXAMPLE 2.5. Let  $R = \mathbb{Q}[x, y]$  and  $I = (x^3, x^2y^2, y^7)$ . Using the fact that the integral closure of a monomial ideal corresponds to the integer lattice points in the convex hull of the exponent vectors of the ideal, this example is easily computed by hand. The first two commands load files named Ideal-Normal.m2 and blowup.m2 which are the programs given in the appendix.

```
i1 : load "IdealNormal.m2"; load "blowup.m2";
--loaded IdealNormal.m2
--loaded blowup.m2
i2 : R = QQ[x,y]; I = ideal(x^2,x*y^4,y^5);
o3 : Ideal of R
i4 : time idealIC(I)
        -- used 0.98 seconds
```

2 3 5 o4 = ideal (x , x\*y , y )

```
o4 : Ideal of R
```

```
Computing the integral closure of an ideal in SINGULAR uses the library reesclos.lib which we used in Example 2.4. The library must be loaded if it has not already been.
```

```
> ring R = 0,(x,y),dp; ideal I = x2,xy4,y5;
> list J = normalI(I); J;
[1]:
    _[1]=x2
    _[2]=y5
    _[3]=-xy3
    The output following [1]: is the generators of T.
    EXAMPLE 2.6. Let R = Q[x,y,z] and I = (y<sup>6</sup> + x<sup>2</sup>z, -x<sup>6</sup> + y<sup>4</sup>z<sup>2</sup>).
i5 : R = QQ[x,y,z, MonomialSize => 16];
i6 : I = ideal(y<sup>6</sup>+x<sup>2</sup>zz, -x<sup>6</sup>+y<sup>4</sup>z<sup>2</sup>); time idealIC(I)
o6 : Ideal of R
    _-- used 3.6 seconds
```

```
A. TAYLOR
```

```
6 2 6 4 2 5 4 2 3
o7 = ideal (y + x z, x - y z , x y + x*y z)
o7 : Ideal of R
> ring R=0,(x,y,z),dp; ideal I=y6+x2z,-x6+y4z2;
> list J=normalI(I); J;
[1]:
    _[1]=y6+x2z
    _[2]=-x6+y4z2
    _[3]=x5y4+xy2z3
```

These examples show that both MACAULAY 2 and SINGULAR can compute the integral closure of a 2 generated ideal in 3 variables, but an ideal with three generators will often cause problems. For example, if  $R = \mathbb{Q}[x, y, z]$  and  $I = (y^6 + x^2z, -x^6 + y^4z^2, x^3y - z^3y)$  then MACAULAY 2 will give a monomial overflow error and SINGULAR runs for about 7.1 hours and uses up the memory available on this machine. But, with two variables and two generators we can find a troublesome ideal in degree as low as seven. If  $R = \mathbb{Q}[x, y]$  and  $I = (y^7 + x^4, -y^6 + xy^4)$  then MACAULAY 2 finishes in 905.29 CPU seconds and uses about 66% of the memory. The ideal we get is

$$\overline{I} = (x^2y^3 + x^4, x^3y^2 - x^4, x^4y + 39x^3y^2 - 38x^4, x^5 - x^4, y^6 - xy^4, xy^5 + x^4).$$

We ran this same example in SINGULAR and after 80,836.49 CPU seconds the machine quit the computation after using all of the memory. Both programs struggle with various computations of ideal integral closure due to computing the integral closure of the blow-up ring which has more variables than the original ring. Thus, while it is possible to compute the integral closure of some ideals using this method, for most cases it is impractical and the myriad of papers dealing with special cases must be consulted.

# 3. Appendix

The program idealIC, below, computes the integral closure of an ideal in MACAULAY 2. This is the program used to compute the closures in Examples 2.5, 2.6. Except for ICfractionsLong all of the functions used in idealIC are self-explanatory, are commented, or are clearly explained in the MACAULAY 2 documentation. ICfractionsLong is similar to the function ICfractions used in Example 2.4 which computes the normalization of A and then returns a minimal generating set for  $\overline{A}$  as an algebra over A. During the normalization computation fractions are computed that may be extraneous and while ICfractions only returns a minimal set, ICfractionsLong keeps track of all the fractions generated by the computation. To ensure that the entire degree one component of the integral closure of the Rees algebra is computed, ICfractionsLong is used rather than ICfractions.

```
idealIC = method()
idealIC(Ideal) := Ideal => (I) -> (
    R := ring I;
    n1 := numgens R;
    J1 := blowup(I); --defining ideal of blow-up
```

14

15

```
R2 := ring J1;
n2 := numgens R2;
S := R2/J1; -- the blow-up
Sfrac1 := first entries ICfractionsLong S;
-- The slow part is ICfractionsLong(S), as expected.
Sfrac2 := apply(#Sfrac1-n2, i-> Sfrac1#i);
toLift := select(Sfrac2, i-> (degree i)#1 == 1);
-- toLift is the set of elements in the normalization
-- of the Rees algebra that generate the degree one
-- component.
VarImage := flatten append (gens R, first entries gens I);
-- We use VarImage to define the map from R2 -> R needed
-- to lift the fractions back to R.
LiftMap := map(R,R2,VarImage);
NewNums := apply(toLift, i-> LiftMap(
          substitute(numerator i, R2)));
NewDenoms := apply(toLift, i-> LiftMap(
          substitute(denominator i, R2)));
NewGens := apply(#toLift, i-> substitute(
          (NewNums#i)/(NewDenoms#i),R));
ideal mingens (I + ideal(NewGens))
)
```

A program for computing the Rees algebra R[tI] in MACAULAY 2 which is used in the program IdealIC give above.

```
blowup = method(Options => {VarName => Y})
blowup(Ideal) := o > (J) > (
     -- Input: J is any ideal.
     -- Output: The result is the defining ideal of the
                 blowup algebra R[tJ] where R is the ring
     ___
                 of J.
     ___
     -- METHOD: We construct a polynomial ring
                 R[t,y_1,..,y_n] where n is the number of
     ___
                 generators of J. We then construct the ideal
                 (Y_1-tJ_1,\ldots,Y_n-tJ_n). Then R[tJ] is
                 isomorphic to the polynomial ring
     ___
                 R[Y_1, \ldots, Y_n] mod the out put of this
                 algorithm.
     ___
     R := ring(J);
     n1 := numgens(J);
     n2 := numgens(R);
     Degs1 := flatten degrees source gens J;
     -- Degs1 are the degrees of the generators of J.
     Degs1a := apply(n1,i->1+Degs1_i);
     Degs2 := flatten ((monoid R).Options.Degrees);
     -- Degs2 is the degrees of the variables of R.
     Degs := join({1},Degs2,Degs1a);
     S := coefficientRing(R)[t,gens R,
          (o.VarName)_(1)..(o.VarName)_(n1),
```

```
MonomialOrder => Eliminate 1, Degrees => Degs];
J1 := substitute(J,S); -- Put J in the bigger ring S.
M := matrix{apply(n1,i-> S_(i+n2+1)-S_0*J1_i)};
-- This is the matrix (Y_1-tJ_1,...,Y_n-tJ_n)
K := gb(M);
-- Next eliminate t.
L := ideal(selectInSubring(1,gens(K)));
-- Set the Multidegrees.
Degs1b := apply(n1,i->join({Degs1_i},{1}));
Degs2b := apply(n2,i->join({Degs2_i},{0}));
Degsb := join(Degs2b,Degs1b);
Sb := coefficientRing(R) [gens R,
      (o.VarName)_1..(o.VarName)_(n1),
      MonomialOrder => ProductOrder{n2,n1},
      Degrees => Degsb];
trim(substitute(L,Sb))
)
```

### Acknowledgements

I thank Anna Guerrieri for encouraging me to write this article and Mike Stillman and Wolmer Vasconcelos for their helpful conversations. I thank David Eisenbud and C. Musili for giving me the opportunity to attend the conference in Hyderabad, India.

# References

- F. Catanese, Commutative algebra methods and equations of regular surfaces, Algebraic geometry, Bucharest 1982 (Bucharest, 1982), Lecture Notes in Math., no. 1056, Springer, Berlin, (1984), 68–111.
- [2] W. Decker, G.-M. Greuel, T. de Jong and G. Pfister, *The normalization: a new algorithm, implementation and comparisons*, Computational methods for representations of groups and algebras (Essen, 1997), Progr. Math. 173, Birkhäuser, Basel, (1999), 177–185.
- [3] D. Eisenbud, C. Huneke and B. Ulrich, What is the Rees algebra of a module?, Preprint.
- [4] D. Eisenbud, Commutative Algebra with a View Toward Algebraic Geometry, Graduate Texts in Math. no. 150, Springer-Verlag, New York, (1996).
- [5] D. Grayson and M. Stillman, MACAULAY 2, a software system for research in algebraic geometry. Available at http://www.math.uiuc.edu/Macaulay2.
- [6] H. Grauert and R. Remmert, Analytische Stellenalgebren, Die Grundlehren der mathematischen Wissenschaften, no. 176, Springer-Verlag, Berlin-New York, 1971.
- [7] H. Grauert and R. Remmert, *Coherent analytic sheaves*, Die Grundlehren der Mathematischen Wissenschaften, no. 265, Springer-Verlag, Berlin, 1984.
- [8] G.-M. Greuel, Computer Algebra and Algebraic Geometry-Achievements and Perspectives, J. Symbolic Comput. 30 (2000), no. 3, 253–289.
- [9] G.-M. Greuel and G. Pfister, A Singular introduction to commutative algebra, Algorithms and Computations in Mathematics no. 10, Springer-Verlag, New York, 2002.
- [10] G.-M. Greuel, G. Pfister, and H. Schönemann, SINGULAR 2.0. A Computer Algebra System for Polynomial Computations. Centre for Computer Algebra, University of Kaiserslautern (2001). http://www.singular.uni-kl.de.
- [11] G.-M. Greuel and G. Pfister, normal.lib. A SINGULAR 2.0 library for computing the normalization of affine rings (2001).

16

- [12] T. de Jong, An Algorithm for computing the integral closure, J. Symbolic Comput. 26 (1998), no. 3, 273-277.
- [13] H. Matsumura, Commutative Ring Theory, 2<sup>nd</sup> ed., Cambridge Studies in Advanced Mathematics, no. 8, Cambridge University Press, New York, 1986.
- [14] G. Smith and B. Sturmfels, *Teaching the Geometry of Schemes*, Computations in Algebraic Geometry with Macaulay 2, Algorithms and Computations in Mathematics no. 8, Springer-Verlag, Heidelberg, (2002), 55–70.
- [15] W. Vasconcelos, Computational Methods in Commutative Algebra and Algebraic Geometry, Algorithms and Computations in Mathematics no. 2, Springer-Verlag, Berlin, 1998.
- [16] W. Vasconcelos, Computing the integral closure of an affine domain, Proc. Amer. Math. Soc. 113 (1991), no. 3, 633–638.
- [17] W. Vasconcelos, Divisorial extensions and the computation of integral closures, J. Symbolic Comput. 30 (2000), no. 5, 595–604.
- [18] W. Vasconcelos, *The Integral Closure*, Commutative Algebra (Trieste, 1992), World Sci. Publishing River, Edge, NJ, (1994), 263–290.

DEPARTMENT OF MATHEMATICS, RUTGERS UNIVERSITY, PISCATAWAY, NJ 08854 E-mail address: ataylor@math.rutgers.edu