## The generation of entangled photon states by using linear optical elements

XuBo Zou, K. Pahlke and W. Mathis Electromagnetic Theory Group at THT, Department of Electrical Engineering, University of Hannover, Germany

November 1, 2018

## Abstract

We present a scheme to generate the polarization-entangled two-photon state  $\frac{1}{\sqrt{2}}(|H\rangle|V\rangle + |V\rangle|H\rangle)$ , which is of much interest in the field of quantum information processing. Furthermore we demonstrate the capability of this concept in respect of a generalization to entangle N-photon states for interferometry and lithography. This scheme requires single-photon sources, linear optical elements and a multi-fold coincidence detection.

PACS number(s):03.65.Ud, 42.50.-p

The generation of entangled quantum states plays a prominent role in quantum optics. An experimental realization in this context can be achieved with trapped ions [1], Cavity QED [2] or Bose-Einstein condenses [3]. Experiments with polarizationentangled photons opened a whole field of research. Polarization-entanglement was used to test the Bell-inequality [4] and to implement quantum information protocols like quantum teleportation [5], quantum dense coding [6] and quantum cryptography [7]. The experimental generation of GHZ-states of three or four photons were reported [8]. These polarization-entangled photon states were only been produced randomly, since there is no way of demonstrating that polarization entanglement was generated without measuring and destroying the outgoing state [9]. Some quantum protocols like error correction were designed for maximally entangled quantum states without random entanglement [10]. Thus, a photon source is needed, which produces maximally polarization-entangled outgoing photons. Remarkably, efficient quantum computation with linear optics was put forward [11]. Such schemes can be used directly to generate polarization-entangled quantum states. It was suggested to arrange an array of beam splitters in order to implement a basic non-deterministic gate [11]. A feasible linear optical scheme [12] was proposed to generate polarization-entanglement by making use of single-photon quantum non-demolition measurements based on an atom-cavity system [13]. There is a potential interest in generating entanglement of optical modes with greater photon numbers. Entangled N-photon states of the form

$$\Psi = \frac{1}{\sqrt{2}} (|0,N\rangle + |N,0\rangle) \tag{1}$$

are of much interest in respect of the phase sensitivity in a two-mode interferometer [14]. They should allow a measurement at the Heisenberg uncertainty limit [15]. Recently it was shown that such states allow sub-diffraction limited lithography [16]. In the case of N = 2 the entangled N-photon state (1) can be generated easily by using linear optical elements. For higher values of N, a scheme was proposed by using non-linear media [17]. It was assumed that the generation of quantum states of this type is possible by using linear optical schemes. Recently, the first linear optical scheme was proposed to entangle four-photon states [18]. Furthermore, it was shown that any two-mode photon states can in principle be generated with a linear optical scheme based on non-detection [19, 20]. Kok et al presented a linear optical scheme to generate the state (1), which is based on a N-fold photon coincidence detection.

At first we show that two-photon polarization entanglement can be generated with our scheme, if the initial state is  $|H\rangle_1|H\rangle_2$ . We use the abbreviations H and V to denote the horizontal and vertical linear polarization of each photon. In Figure 1 the required symmetric experimental setup of our protocol is shown. Two optical input modes are entangled by the beam splitter BS. In each of these entangled branches a polarization rotator, a single-photon injection block and another rotator is inserted. Finally these branches pass a polarization beam splitter PBS. This setup looks like an optical interferometer with the possibility to vary the angle of the rotators continuously, to inject a photon and to get classical information with the aid of the detectors  $D_1$  and  $D_2$ .

In the following the performance of this arrangement of linear optical devices will be analyzed in detail. The action of the symmetric beam splitter BS can be described by the unitary operator

$$U_{bs} = \exp\left[\frac{\pi}{4} (a_{1H} a_{2H}^{\dagger} - a_{1H}^{\dagger} a_{2H})\right].$$
(2)

After passing the beam splitter BS the initial state is transferred into the other mode

$$\Psi_1 = \frac{1}{\sqrt{2}} (|2H\rangle_1 |0\rangle_2 - |0\rangle_1 |2H\rangle_2).$$
(3)

The two output modes of the beam splitter pass through two polarization rotators with the rotation angle  $\theta$ . These linear optical devices can be described by the transformation

$$\begin{array}{rcl}
a_{H}^{\dagger} & \to & (\cos\theta)a_{H}^{\dagger} + (\sin\theta)a_{V}^{\dagger}; \\
a_{V}^{\dagger} & \to & (\cos\theta)a_{V}^{\dagger} - (\sin\theta)a_{H}^{\dagger}.
\end{array} \tag{4}$$

In order to obtain the maximum efficiency of our scheme the rotation angles  $\theta$  are calibrated to fulfill  $\cos \theta = \sqrt{\frac{1}{3}}$ . The two-photon state transforms to

$$\Psi_{2} = \frac{\sqrt{2}}{3} [0.5|2H\rangle_{1'}|0\rangle_{2'} + |HV\rangle_{1'}|0\rangle_{2'} + |2V\rangle_{1'}|0\rangle_{2'} -0.5|0\rangle_{1'}|2H\rangle_{2'} - |0\rangle_{1'}|HV\rangle_{2'} - |0\rangle_{1'}|2V\rangle_{2'}].$$
(5)

The two output modes of the rotators pass two polarization beam splitters:  $PBS_1$  and  $PBS_2$ . Since the polarization beam splitter transmit only the horizontal polarization

component and reflect the vertical component, the state evolves into

$$\Psi_{3} = \frac{\sqrt{2}}{3} [0.5|2H\rangle_{3} + |H\rangle_{3}|V\rangle_{4} + |2V\rangle_{4} -0.5|2H\rangle_{5} - |H\rangle_{5}|V\rangle_{6} - |2V\rangle_{6}].$$
(6)

The scheme uses the output modes 4 and 6 to couple separately a single-photon source as the second input port of the symmetric beam splitters  $BS_1$  and  $BS_2$ . We assume that these single-photon sources are in the single-photon state  $|1\rangle$ . If the two-fold coincidence detection results in one photon in each detector  $D_1$  and  $D_2$  the quantum state is projected into

$$\Psi_{4} = \frac{1}{2} [|2H\rangle_{3} - |2V\rangle_{4'} - |2H\rangle_{5} + |2V\rangle_{6'}].$$
(7)

Conditioned on this outcome the polarization beam splitters  $PBS_3$  and  $PBS_4$  transform the two-photon quantum state into

$$\Psi_5 = \frac{1}{2} [|2H\rangle_7 - |2V\rangle_7 -|2H\rangle_8 + |2V\rangle_8].$$
(8)

These two output modes 7 and 8 pass through two polarization rotators which are calibrated to fulfill:  $\theta_2 = \frac{\pi}{4}$ . Finally the quantum state

$$\Psi_{6} = \frac{1}{\sqrt{2}} [|HV\rangle_{7'} - |HV\rangle_{8'}]$$
(9)

is incident on a polarization beam splitter in order to obtain the two-photon polarization entangled quantum state

$$\Psi_7 = \frac{1}{\sqrt{2}} (|H\rangle|V\rangle - |V\rangle|H\rangle) \,. \tag{10}$$

In order to present the principle idea of our scheme to generate entangled N-photon states we introduce in Figure 2 simple building blocks  $\Theta$  as optical two-mode devices. Two separate single-photon injections and two photon-number detectors are involved in this device. In the following we will demonstrate the generalization capability of the concept to entangle N-photon states. A detailed estimation of the generalized scheme will be presented in the following. It will be shown how the quantum state (1) can be generated and how different terms of the N-photon state can be deleted. We consider an arbitrary N-photon state

$$\Psi_{in} = \sum_{n=0}^{N} C_n |n\rangle_a |N - n\rangle_b \tag{11}$$

to be the input mode of the basic block  $\Theta$ . In contrast to the previously analyzed two-photon system we label in Figure 2 the four input modes 1, 2, 3, 4 with the letters

a, b, c, d. In order to formulate the functionality of this basic block for arbitrary photon number states transformation we relate to these modes the annihilation operators a, b, c, d and the creation operators  $a^{\dagger}, b^{\dagger}, c^{\dagger}, d^{\dagger}$ . The interaction with the beam splitters  $BS_1$  and  $BS_2$  can be formulated with the unitary operators:

$$U_1 = \exp[\theta(ac^{\dagger} - a^{\dagger}c)] \tag{12}$$

$$U_2 = \exp[\theta(bd^{\dagger} - b^{\dagger}d)].$$
(13)

The output of these beam splitters is the four-mode state

$$\Phi = U_1 U_2 |\Psi_{in}\rangle |1\rangle_c |1\rangle_d = \sum_{n=0}^N \frac{C_n}{\sqrt{n!(N-n)}} (\cos\theta a^{\dagger} + \sin\theta c^{\dagger})^n (\cos\theta c^{\dagger} - \sin\theta a^{\dagger}) \\ \times (\cos\theta b^{\dagger} + \sin\theta d^{\dagger})^{N-n} (\cos\theta d^{\dagger} - \sin\theta c^{\dagger}) |0\rangle_a |0\rangle_b |0\rangle_c |0\rangle_d \,.$$
(14)

The function of the building block is based on post-selection. A two-fold coincidence detection projects the four-mode state  $\Phi$  into the two-mode states  $\Psi$ . Conditioned on the coincidence of one photon in each detector the (not normalized) quantum state

$$\Psi = \sum_{n=0}^{N} C_n \cos^{N-2} (\cos^2 \theta - n \sin^2 \theta) (\cos^2 \theta - (N-n) \sin^2 \theta) |n\rangle_a |N-n\rangle_b$$
(15)

is generated. We intend to demonstrate that the term  $|i\rangle_a|N-i\rangle_b$  and the term  $|N-i\rangle_a|i\rangle_b$  of the input state (11) (with n = i and n = N - i) can be deleted by changing the value  $\theta$  of the beam splitters appropriately. This can be achieved by choosing the parameter  $\theta$  to satisfy  $\tan \theta = \sqrt{i}$ .

Now we propose the generation of the maximally entangled N-photon state (1) by arranging the building blocks  $\Theta$  like it is shown in Figure 3. For simplicity, we consider the 2N-photon state  $\frac{1}{\sqrt{2}}(|0,2N\rangle + |2N,0\rangle)$ , but the same scheme can also be used to generate the entangled 2N + 1-photon state  $\frac{1}{\sqrt{2}}(|0,2N+1\rangle + |2N+1,0\rangle)$ . As the input mode of the symmetric beam splitter BS we use N photons in the mode 1 and N photons in the mode 2. The output of this first beam splitter is the entangled 2N-photon state:

$$\Psi = \frac{1}{2^N} \sum_{m=0}^{N} (-1)^m \frac{\sqrt{(2m)!(2N-2m)!}}{m!(N-m)!} |2N-2m\rangle_{1'} |2m\rangle_{2'} \,. \tag{16}$$

In order to generate the maximally entangled state (1) M basic elements are required  $\{M = N/2, \text{ if } N \text{ is even}; M = (N-1)/2, \text{ if } N \text{ is odd}\}$ . Conditioned on the 2M-fold coincidence detection the state  $\Psi = \frac{1}{\sqrt{2}}(|0,2N\rangle + |2N,0\rangle)$  can be generated, if the parameters are chosen appropriately:  $\tan \theta_i = \sqrt{2i}, (i = 1, \dots, M)$ . The probability of this outcome is  $\frac{(2N)![(2N-2)!!]^2[(N-1)!!]^{2N}}{2^{2N-1}(N!)^4(N!!)^{2N}}$ , if N is odd. Otherwise the probability of this outcome will be  $\frac{(2N)![(2N-2)!!]^2[(N+1)!!]^{2N}}{2^{2N-1}((N-1)!)^2((N+1)!!)^{2(N)}}$ . In order to demonstrate, how entangled 2N + 1-photon states can be generated, we

In order to demonstrate, how entangled 2N + 1-photon states can be generated, we require that the input of the symmetric beam splitter is in a quantum state with 2N+1 photons in the mode 1 and 0 photons in the mode 2. The spatially separated output

photons of the beam splitter are incident on N basic elements whose parameter is chosen to be  $\tan \theta_i = \sqrt{i}$ ,  $(i = 1, \dots, N)$ . Based on the 2N-fold photon coincidence detection, the maximally entangled 2N + 1-photon state (1) will be obtained. The probability of success is  $\frac{[(2N)!]^2}{4^N(N+1)^{2N+1}[N!(N+1)!]^2}$ .

In summary, we have suggested a feasible scheme to prepare polarization-entangled quantum states and entangled N-photon states by using linear optical devices. In the case of the polarization-entangled two-photon states the probability of the outcome will be 1/18. This is a slightly smaller value than 1/16, which the scheme with the non-deterministic gate [11] makes possible. But the experimental setup of our scheme is simpler. Instead of four detectors only a two-fold coincidence detection is required. Thus, the number of detectors is reduced to the half. In the case of entangled 2N-photon states it is shown that not more than N detectors are required, which is definitely less than other schemes [19, 20, 21] need. An entangled 6-photon state can be generated with the probability of 9.7%. This probability of the outcome is three times bigger than that of the scheme [19] and much bigger than that of the schemes [20, 21].

A generalization to a multi-mode block can be made easily, because the building blocks, which are introduced with the Figure 2, don't couple the input modes. The multi-photon coincidence detection requires only the classical information, which each detector provides. This is a main difference to the building blocks, which Dowling et al. suggested in their paper [21]. In our scheme entanglement is only generated in the first beam splitter, which is shown in Figure 3. Thus, four-mode entangled photon states in the form of  $\frac{1}{2}(|N\rangle|N-m\rangle|0\rangle|0\rangle + |N-m\rangle|N\rangle|0\rangle|0\rangle + |0\rangle|0\rangle|N\rangle|N-k\rangle + |0\rangle|0\rangle|N-k\rangle|N\rangle$ ) can be generated within the generalized concept. These quantum states were employed to create two dimensional patterns on a suitable substrate in quantum optical lithography [16].

One of the difficulties of our scheme in respect to an experimental demonstration consists in the requirement on the sensitivity of the detectors. Other schemes [18, 21], which are based on a multi-fold coincidence detection, pose the same requirements on the capability of the detectors. Recently, the experimental techniques for singlephoton detection made tremendous progress. A photon detector based on a visible light photon counter was reported, which can distinguish between a single-photon incidence and the two-photon incidence with high quantum efficiency, good time resolution and low bit-error rate [22]. Another difficulty is the availability of photon-number sources. Currently available triggered single-photon sources operate by means of fluorescence from a single molecule [23] or a single quantum dot [24, 25] and they exhibit very good performance. However, in our scheme, in order to generate entangled photon state, we need a synchronized arrival of many photons into input ports of many beam splitters, which will be experimentally challenging. However, the generated entangled-photon states can act as a kind of valuable source for quantum computation and quantum communication.

## References

- Q. A. Turchette et al, Phys. Rev. Lett. 81, 1525 (1998); K. Mølmer and A. Sørensen, Phys. Rev. Lett. 82, 1835 (1999); C. A. Suckett et al, Nature(London), 404, 256 (2000).
- [2] A. Rauschenbeutel et al, Science. **288**, 2024 (2000).
- [3] A. Sørensen, L. M. Duan, J. I. Cirac and P. Zoller, Nature(London) 409 63 (2001);
   M. G. Moore and P. Meystre, Phys. Rev. Lett. 85, 5026 (2000).
- [4] D. Bouwmeester, A. Ekert and A. Zeilinger, The physics of Quantum Information (Springer-Verlag, Berlin, 2000)
- [5] D. Bouwmeester et al, Nature(London) **390** 575 (1997)
- [6] K. Mattle et al, Phys. Rev. Lett. **76**, 4656 (1996).
- [7] D. S. Naik et al Phys. Rev. Lett. 84, 4733 (2000); W. Tittel et al Phys. Rev. Lett. 84, 4737 (2000).
- [8] D. Bouwmeester et al., Phys. Rev. Lett. 82, 1345 (1999); J. W. Pan et al, Phys. Rev. Lett. 86, 4435 (2001).
- [9] P. Kok and S. Braunstein, quant-ph/0001080
- [10] D. Bouwmeester, quant-ph/0006108
- [11] E. Knill, R. Laflamme and G. Milburn, Nature(London) 409, 46 (2001).
- [12] Z. B. Chen, J. W. Pan and Y. D. Zhang, quant-ph/0105100
- [13] P. Grangier, J. A. Levenson and J. P. Poizat, Nature(London) **396**, 537 (1998).
- [14] Christopher C. Gerry, Phys. Rev. A **61** 043811 (2000)
- [15] D. J. Wineland et al. Phys. Scr. T 76, 1471 (1998); J. J. Bollinger et al Phys. Rev. A 54, R4649 (1996).
- [16] A. N. Boto et al, Phys. Rev. Lett. 85, 2733 (2000); Pieter Kok et al, Phys. Rev. A 63, 063407 (2001)
- [17] Christopher C. Gerry, Phys. Rev. A 65 033822 (2002)
- [18] Hwang Lee, Pieter Kok, Nicolas J. Cerf, Jonathan P. Dowling, quant-ph/0109080.
- [19] Jaromir Fiurasek, quant-ph/0110138
- [20] XuBo Zou, K. Pahlke and W. Mathis, quant-ph/0110149,
- [21] Pieter Kok, Hwang Lee, Jonathan P. Dowling, quant-ph/0112002

- [22] Jungsang Kim, Shigeki Takeuchi, Yoshihisa Yamamoto, and Henry H. Hogue, Applied Physics Letters, 74, 902 (1999)
- [23] Christian Brunel, Brahim Lounis, Philippe Tamarat, and Michel Orrit, Phys. Rev. Lett. 83, 2722 (1999).
- [24] Charles Santori et al., Phys. Rev. Lett. 86, 1502 (2001)
- [25] P. Michler et al, Science 290, 2282(2000)

Figure 1: This figure shows the required experimental setup to generate polarizationentangled two-photon states. The polarization beam splitters  $(PBS, PBS_i(i=1,2,3,4))$ transmit *H*-photons and reflect *V*-Photons. Four polarization rotators  $R_i$  (i=1,2,3,4) are required. *BS* and *BS*<sub>i</sub>(i=1,2) denote symmetric beam splitters. The scheme requires three photon number detectors  $D_1$  and  $D_2$ .

Figure 2: The basic element to entangle N-photon states.  $\theta$  denotes the parameter of the beam splitter.

Figure 3: If M basic blocks are arranged N-photon states can be entangled in a very efficient way. Therefore a the choice of the parameter  $\theta_i$  and a 2M-fold coincidence detection is needed.







