

The generation of an entangled four-photon W -state by using linear optical elements

XuBo Zou, K. Pahlke and W. M. Mathis

Electromagnetic Theory Group at THT,
Department of Electrical Engineering, University of Hannover, Germany

Abstract

We present a scheme to produce an entangled four-photon W -state by using linear optical elements. The symmetrical setup of linear optical elements consists of four beam splitters, four polarisation beam splitters and four mirrors. A photon EPR-pair and two single-photon sources are required as the input modes. The projection on the W -state can be made by a four-photon coincidence measurement. Further on we show, that by means of a horizontally oriented polarizer in front of one detector the W -state of three photons can be generated.

PACS number: 03.65.Ta, 03.67.-a, 42.50.Ar

The generation of entangled states plays a central role in quantum optics. An experimental realization in this context can be achieved with trapped ions [1], cavity-QED [2] and Bose-Einstein condensates [3]. Many schemes were proposed for the generation of entangled states of atoms [4]. The GHZ-state was experimentally demonstrated with a system of four trapped ions and with a system of three atoms and a cavity [5] [2]. Experiments with entangled photons open a broad field of research. Entangled photon states can be used to test Bell's inequality [6] or to implement quantum information protocols for quantum teleportation [7], quantum dense coding [8] and quantum cryptography [9]. An experimental realization of GHZ-states by means of three or four photons was experimentally demonstrated [10]. Efficient quantum computation with linear optics was put forward [13]. More recently, a feasible linear optical scheme [14] was proposed to produce entangled N -photon states of the form $\frac{1}{\sqrt{2}}(|0\rangle^N |1\rangle + |1\rangle^N |0\rangle)$ via linear optical elements. The incentive to produce entangled states of spin- s objects ($s > 1/2$) increased significantly in the context of quantum communication and quantum information processing [15, 16]. A scheme was proposed [17] to generate an entangled four-photon state $\frac{1}{\sqrt{3}}(|2;0;2;0\rangle + |1;1;1;1\rangle + |0;2;0;2\rangle)$, which is equivalent to two maximally entangled spin-1 particles. Dür et al. [18] demonstrated the violation of the Bell inequality by this kind of multiphoton states. It was shown that there exist two inequivalent classes of three-qubits entangled states, namely the GHZ-state $|\text{GHZ}\rangle = \frac{1}{\sqrt{2}}(|111\rangle + |000\rangle)$ and the W -state $|\text{W}\rangle = \frac{1}{\sqrt{3}}(|100\rangle + |010\rangle + |001\rangle)$, which are assisted under local operation by classical communication [19]. Recently a different set of Bell inequality is considered with the purpose of illustrating some difference between the violation of local realism exhibited by the GHZ and W state [20]. A W -state generation scheme of systems of three or four qubits was proposed [21]. In that paper

the Heisenberg model was used to generate the W -state of three or four atoms. We propose a scheme to generate a W -state

$$|W\rangle = \frac{1}{2}(|HHHV\rangle + |HHVH\rangle + |HVHH\rangle + |VHHH\rangle) \quad (1)$$

of four photons by means of linear optical elements.

An EPR-source $|EPR\rangle$ is used to generate two entangled branches of the symmetric experimental setup. These two branches are denoted by the mode 1 and the mode 2. Two single-photon sources are injected in order to generate an entangled four-photon state. A four-photon coincidence detection projects this state on the W -state.

In the following we present a detailed analysis of the proposed scheme. The experimental setup is shown in Figure 1. The EPR-source generates the input state $|EPR\rangle = (|H_1H_2\rangle + |V_1V_2\rangle)/\sqrt{2}$. In order to inject two further photons in this arrangement of linear optical devices we use two single-photon sources: $|e\rangle = |H_e\rangle$ and $|f\rangle = |H_f\rangle$. The single-photon input modes e and f are horizontally polarized. The two-photon injector consists of four polarization beam splitters PBS_1 , two beam splitter BS_3 and four mirrors. Since polarization beam splitter transmit the horizontal polarization and reflect vertical polarization, the two polarization beam splitters PBS_1 and PBS_2 transform the EPR-state $|EPR\rangle$ into

$$\frac{1}{2}(|H_bV_c\rangle + |V_aH_d\rangle) : \quad (2)$$

Notice, that the modes b and d pass through the beam splitters BS_1 and BS_2 , and that these beam splitters are connected with the single-photon input modes e and f. The result of the two-photon injection at the beam splitters BS_1 and BS_2 is

$$\begin{aligned} & (|H_bV_c\rangle|H_eH_f\rangle + |V_aH_d\rangle|H_eH_f\rangle) \cos^2 \theta \\ & + (|H_bV_c\rangle|H_eH_f\rangle + |V_aH_d\rangle|H_eH_f\rangle) \cos 2\theta \cos \theta \\ & + (|H_bV_c\rangle|H_eH_f\rangle + |V_aH_d\rangle|H_eH_f\rangle) \cos 2\theta \sin \theta \\ & + (|V_c\rangle|H_eH_f\rangle + |V_a\rangle|H_eH_f\rangle) \cos^2 \theta \\ & (|H_bV_c\rangle|H_eH_f\rangle - |V_aH_d\rangle|H_eH_f\rangle) \cos^2 \theta \sin \theta \\ & (|V_c\rangle|H_eH_f\rangle + |V_a\rangle|H_eH_f\rangle) \cos \theta \sin^2 \theta : \end{aligned} \quad (3)$$

The reflectance $\sin^2 \theta$ and the transmittance $\cos^2 \theta$ of these beam splitters are the same, since the same angle θ is chosen. This coefficient will be determined later. This four-photon state interacts with the two polarization beam splitters PBS_3 and PBS_4 , which transmit the horizontal polarization and reflect the vertical polarization state. This method of a two-photon injection on the EPR-modes 1 and 2 results in the four-photon state

$$\begin{aligned} & (|H_1H_2\rangle|H_eH_f\rangle + |V_1V_2\rangle|H_eH_f\rangle) \cos^2 \theta \\ & + (|H_1H_2\rangle|H_eH_f\rangle + |V_1V_2\rangle|H_eH_f\rangle) \cos 2\theta \cos \theta \\ & + (|H_1H_2\rangle|H_eH_f\rangle + |V_1V_2\rangle|H_eH_f\rangle) \cos 2\theta \sin \theta \\ & + (|V_2\rangle|H_eH_f\rangle + |V_1\rangle|H_eH_f\rangle) \cos^2 \theta \sin \theta \\ & (|H_1H_2\rangle|H_eH_f\rangle + |V_1V_2\rangle|H_eH_f\rangle) \cos^2 \theta \sin \theta \\ & (|V_2\rangle|H_eH_f\rangle + |V_1\rangle|H_eH_f\rangle) \cos \theta \sin^2 \theta : \end{aligned} \quad (4)$$

This expression shows the generated four-photon state explicitly in terms of the input modes $(1;2;e;f)$. In order to perform a projection on the W -state a four-photon

coincidence detection is needed. This can be done by splitting the branches 1 and 2 separately by the beam splitters BS_3 and BS_4 . Since we consider only those terms, which correspond to a 4-photon coincidence detection (one photon in each of the four beams), the state of the system is projected with probability $\cos^2 \sin^4 = 2$ into the W -state

$$\begin{aligned} & (\mathcal{H}_{i_1} \mathcal{H}_{i_3} \mathcal{H}_{i_2} \mathcal{V}_{i_4} + \mathcal{H}_{i_1} \mathcal{H}_{i_3} \mathcal{V}_{i_2} \mathcal{H}_{i_4}) = 2 \\ & + (\mathcal{V}_{i_1} \mathcal{H}_{i_3} \mathcal{H}_{i_2} \mathcal{H}_{i_4} + \mathcal{H}_{i_1} \mathcal{V}_{i_3} \mathcal{H}_{i_2} \mathcal{H}_{i_4}) = 2 : \end{aligned} \quad (5)$$

The probability attains its maximal value $2/27$, if the transmittance of the beam splitter is $\cos^2 = 1/3$.

If a polarizer with horizontal orientation is used in front of detector 1 the four-photon coincidence detection projects into the three-photon state

$$(\mathcal{H}_{i_3} \mathcal{H}_{i_2} \mathcal{V}_{i_4} + \mathcal{H}_{i_3} \mathcal{V}_{i_2} \mathcal{H}_{i_4} + \mathcal{V}_{i_3} \mathcal{H}_{i_2} \mathcal{H}_{i_4}) = \frac{2}{3} : \quad (6)$$

In conclusion, a scheme is presented to produce entangled W -states of four photons based on linear optical devices and a four-photons coincidence detection. Further on we proposed a modification of this symmetric scheme by adding one horizontally oriented polarizer in front of detector D_1 . This breaks the symmetry of the scheme and makes the generation of a W -state of three photons possible. Such multi-photon states may play a crucial role in fundamental tests of quantum mechanics versus local realism and in many quantum information and quantum computation schemes.

This scheme requires two single-photon sources and one two-photon EPR-state source. If ideal detectors are assumed, the efficiency of this W -state generation scheme is $2/27$, but the problem of input signal generation (four photons) has to be taken into account. The two single-photon sources can for example consist of two modes generated by a nonlinear crystal, which have a low production probability [22]. Other triggered single photon sources of very good performance operate by means of fluorescence from a single molecule [23] or a single quantum dot [24] [25]. However, the synchronized arrival of the required number of photons on the input ports of our scheme is experimentally challenging.

References

- [1] Q. A. Turchette et al, Phys. Rev. Lett. 81, 1525 (1998).
- [2] A. Rauschenbeutel et al, Science. 288, 2024 (2000).
- [3] A. Sørensen, L. M. Duan, J. I. Cirac and P. Zoller, Nature (London) 409 63 (2001); M. G. Moore and P. M. Eystre, Phys. Rev. Lett. 85, 5026 (2000).
- [4] J. I. Cirac and P. Zoller, Phys. Rev. 50, R2799 (1994); T. Pellizzari, S. Gardiner, J. I. Cirac and P. Zoller, Phys. Rev. Lett. 75, 3788 (1995); J. I. Cirac and P. Zoller, Phys. Rev. Lett. 74, 4091 (1995); M. B. Plenio, S. Fi Huelga, A. Beige and P. L. Knight, Phys. Rev. A 59, 2468 (1999). J. I. Bollinger, W. M. Itano, D. J. Wineland, and D. J. Heinzen, Phys. Rev. A 54, R4649 (1996); J. Steinbach and C. C. Gerry, Phys. Rev. Lett. 81, 5528 (1998); K. M. Mørner and A. Sørensen, Phys. Rev. Lett. 82, 1835 (1999); G. J. Milburn, quant-ph/9980037
- [5] C. A. Sackett, D. Kielpinski, B. E. King, G. Langer, V. Meyer, C. J. Myatt, M. Rowe, Q. A. Turchette, W. M. Itano, D. J. Wineland, and C. Monroe, Nature (London) 404, 256 (2000).

- [6] D .Bouwmeester, A .Ekert and A .Zeilinger, The physics of Quantum Information (Springer-Verlag, Berlin, 2000)
- [7] D .Bouwmeester et al , Nature(London) 390 575 (1997)
- [8] K .Mattle et al, Phys. Rev. Lett. 76, 4656 (1996) .
- [9] D .S.Naik et al Phys. Rev. Lett. 84, 4733 (2000); W .Tittel et al Phys. Rev. Lett. 84, 4737 (2000) .
- [10] D .Bouwmeester et al , Phys. Rev. Lett. 82, 1345 (1999); J.W .Pan et al, Phys. Rev. Lett. 86, 4435 (2001) .
- [11] P .Kok and S .Braunstein, quant-ph/0001080
- [12] D .Bouwmeester, quant-ph/0006108
- [13] E . Knill, R . Laamme and G . Milburn, Nature(London) 409, 46 (2001), T C Ralph, A G White, W J Munro, G J Milburn, quant-ph/0108049; Terry Rudolph, Jian-W ei Pan, quant-ph/0108056, XuBo Zou, K .Pahlke, W .M athis, to appear in PRA , quant-ph/0110177
- [14] Hwang Lee, Pieter Kok, Nicolas J. Cerf, Jonathan P. Dowling, quant-ph/0109080 ; Jaromir Fiurasek, quant-ph/0110138 ; XuBo Zou, K .Pahlke and W .M athis, quant-ph/0110168, quant-ph/0110149
- [15] N .Gisin and A .Peres, Phys. Lett. A 162, 15 (1992)
- [16] D .Kaszlikowski, P .Gnascinski, M .Zukowski, W .Miklaszewski, and A .Zeilinger, Phys. Rev. Lett. 85, 4418 (2000) .
- [17] XuBo Zou, K .Pahlke, W .M athis, quant-ph/0111014
- [18] P .D .Dummond, Phys. Rev. Lett. 50, 407 (1983) .
- [19] W .Dr, G .Vidal, and J.I. Cirac, Phys. Rev. A 62, 062314 (2000) .
- [20] Adn Cabello, Phys. Rev. A 65, 032108 (2002) .
- [21] Xiaoguang Wang, Phys. Rev. A 64, 012313 (2001)
- [22] C .K .Hong, Z .Y .Ou, L .Mandel, Phys. Rev. Lett. 59, 2044 (1987)
- [23] Christian Brunel, Brahim Lounis, Philippe Tamarat, and Michel Orrit, Phys. Rev. Lett. 83, 2722 (1999) .
- [24] Charles Santori et al, Phys. Rev. Lett. 86, 1502 (2001)
- [25] P .M ichler et al, Science 290, 2282 (2000)

Figure Captions

Figure 1. The schematic of the W state of four photons. EPR denote entangled two photon state $\frac{1}{\sqrt{2}}(|\psi_1\rangle|\psi_2\rangle + |\psi_2\rangle|\psi_1\rangle)$. PBS_i are polarization beam splitters and BS_i are beam splitters. D_i are photon number detectors.

