

Kontsevich graphs act on Nambu–Poisson brackets, III. Uniqueness aspects (section 4)

November 22, 2024

```
[1]: # 17-09-2024 The code below is a combination of already existing code by R.
      ↪Buring, and adjustments made by F. Schipper
      # (particularly, the biggest adjustments are checking that the basis element(s)
      ↪of the cocycle space are Hamiltonian,
      # commentary and printing of output). It is supplementary material accompanying
      ↪proceedings written for the ISQS28 (Integrable
      #Systems and Quantum Symmetries) conference (see also: arxiv link??).

      # We import the following (see https://github.com/rburing/gcaops) to be able to
      ↪run the code.
      from gcaops.graph.formality_graph import FormalityGraph
      from gcaops.algebra.differential_polynomial_ring import
      ↪DifferentialPolynomialRing
      from gcaops.algebra.superfunction_algebra import SuperfunctionAlgebra
      from gcaops.graph.undirected_graph_complex import UndirectedGraphComplex
      from gcaops.graph.directed_graph_complex import DirectedGraphComplex

      # We start by generating the encodings for the descendants of  $\Gamma_{11}^{2D}$  and
      ↪ $\Gamma_{12}^{2D}$ 
      import itertools

      X_graph_encodings = []
      for (i1,j1,j2,k) in itertools.product([2,5], [1,4], [1,4], [3,6]):
          X_graph_encodings.append((0,1,4,j1,k,5,j2,i1,6))

      for (i1,i2,j1,j2,k) in itertools.product([2,5], [2,5], [1,4], [1,4], [3,6]):
          X_graph_encodings.append((0,i1,4,j1,k,5,j2,i2,6))

      # To move from the encodings of the graphs to the actual graphs, we use the next
      ↪function. The definition splits the
      # encoding by vertex via ;, and then the targets by ,. A graph is returned on 3
      ↪Levi-Civita vertices, 3 corresponding Casimir
      # vertices, 1 sink, and with edges (origin vertex, target vertex).

      def encoding_to_graph(encoding):
```

```

    targets = [encoding[0:3], encoding[3:6], encoding[6:9]]
    edges = sum([(k+1,v) for v in t] for (k,t) in enumerate(targets)), [])
    return FormalityGraph(1, 6, edges)

X_graphs = [encoding_to_graph(e) for e in X_graph_encodings]
print('We have', len(X_graphs), 'graphs.\n')

# Below, we check the how many graphs that were created via the encodings are
# →(non)isomorphic. It does so in the following way:
# for each formality graph in X_graphs, it computes the edges of the canonical
# →form (canonical in the sense that isomorphic
# graphs return the same canonical form) of said formality graph. If a graph
# →with these edges already appears in X_graphs_iso,
# the new (isomorphic) graph is not added to the list. If the graph does not yet
# →appear, it is added to the list. The list is
# indexed by h, NOT by an index from 0,...,40. For this, unmute the line
# →X_graphs_iso=list(X_graphs_iso.values())
X_graphs_iso={}
for g in X_graphs:
    h=tuple(g.canonical_form().edges())
    if not h in X_graphs_iso:
        X_graphs_iso[h]=g
X_graphs_iso=list(X_graphs_iso.values())
print('Lemma 8: There are', len(X_graphs_iso), 'nonisomorphic graphs.\n')

# Create the differential polynomial ring. We are working in 3D, so we only have
# →even coordinates x,y,z and the corresponding
# odd coordinates xi[0], xi[1] and xi[2]. rho is exactly the rho in a 3D
# →Nambu-determinant Poisson bracket,
# (P(f,g)= rho d(f,g,a)/d(x,y,z)), and a is the Casimir. Finally,
# →max_differential_orders tells the programme how many times
# rho and a can be differentiated. The maximum is stipulated by the graphs, as
# →we cannot have double edges. Thus, the
# maximum in degree of each rho vertex is 3. As we will be looking at [[P,X]],
# →we add an extra +1 to the differential orders
# since taking the Schouten bracket with P introduces an extra derivative.
D3 = DifferentialPolynomialRing(QQ, ('rho','a'), ('x','y','z'),
# →max_differential_orders=[3+1,3+1])
rho, a = D3.fibre_variables()
x,y,z = D3.base_variables()
even_coords = [x,y,z]

S3.<xi0,xi1,xi2> = SuperfunctionAlgebra(D3, D3.base_variables())
xi = S3.gens()
odd_coords = xi

```

```

# We now compute the vector fields corresponding to the graphs. E is the Euler
→vector field in the sink (vertex 0), and
# epsilon is the Levi-Civita tensor. Note that we have a Levi-Civita tensor at
→each of the vertices 1, 2, 3. We first compute
# the sign of each term appearing in the formulas, and then compute the
→differential polynomial.
X_vector_fields=[]
E = x*xi[0] + y*xi[1] + z*xi[2]
epsilon = xi[0]*xi[1]*xi[2]
for g in X_graphs:
    term = S3.zero()
    for index_choice in itertools.product(itertools.permutations(range(3)),
→repeat=3):
        sign = epsilon[index_choice[0]] * epsilon[index_choice[1]] *
→epsilon[index_choice[2]]
        vertex_content = [E, S3(rho), S3(rho), S3(rho), S3(a), S3(a), S3(a)]
        for ((source, target), index) in zip(g.edges(), sum(map(list,
→index_choice), [])):
            vertex_content[target] = diff(vertex_content[target],
→even_coords[index])
            term += sign * prod(vertex_content)
    X_vector_fields.append(term)

# We check how many (if any) graphs evaluate to 0.
zeros=X_vector_fields.count(0)
print('There are', zeros, 'graphs that evaluate to 0 under the morphism from
→graphs to multivectors.')

# In case there are graphs that evaluate to 0, the line below shows which graphs
→do so (note that the counting starts from 1!).
print('These graphs are:')
for (k,X) in enumerate(X_vector_fields):
    if X==0:
        print('graph', k+1,)
print()

# The next part is to find out linear relations of the vector fields we just
→computed. We look at the monomials that appear
# in each xi[0], xi[1] and xi[2] parts of the vector field, and store them in
→X_monomial_basis.
X_monomial_basis = [set([]) for i in range(3)]
for i in range(3):
    for X in X_vector_fields:
        X_monomial_basis[i] |= set(X[i].monomials())
X_monomial_basis = [list(b) for b in X_monomial_basis]
X_monomial_count = sum(len(b) for b in X_monomial_basis)

```

```

# Next, we use this monomial basis to create a matrix that identifies each
→vector field by the monomials that appear in it.
X_evaluation_matrix = matrix(QQ, X_monomial_count, len(X_vector_fields))
for i in range(len(X_vector_fields)):
    v = vector(QQ, X_monomial_count)
    index_shift = 0
    for j in range(3):
        f = X_vector_fields[i][j]
        for coeff, monomial in zip(f.coefficients(), f.monomials()):
            monomial_index = X_monomial_basis[j].index(monomial)
            v[index_shift + monomial_index] = coeff
            index_shift += len(X_monomial_basis[j])
    X_evaluation_matrix.set_column(i, v)

# We can now detect linear relation by computing the nullity of this matrix
→(Note that we already know of 7 linear relations
# as 7 of the 48 graphs are counted double via an isomorphism.
nullity = X_evaluation_matrix.right_nullity()
print('The vector fields have', nullity, 'linear relations among themselves.\n')

# Unmute the next line if you want to explicitly see the 28 linear relations
→among the vector fields
#print('These relations are expressed by \n', X_evaluation_matrix.right_kernel().
→basis(), '\n')

# We now compute the tetrahedral flow. First, we create the Poisson bivector P
→and check that it satisfies  $[[P, P]] = 0$ .
P = (rho*epsilon).bracket(a)
if P.bracket(P) != 0:
    print('P is not a Poisson bivector. \n')

# Introduce the graph complex, and find the tetrahedron as a graph on 4 Poisson
→vertices and 6 edges in the cohomology. This
# tetrahedron is unoriented, so we orient it. The next step is to make sure that
→the graph is built of wedges. This means
# that there cannot be more than 2 outgoing edges at each vertex. This gives 2
→graphs; one where 3 vertices have 2 outgoing
# edges, and one where 2 vertices have 2 outgoing edges and 2 vertices have 1
→outgoing edge.
# tetrahedron_oriented_filtered.show() gives a drawing of these graphs.
# Finally, the bivector corresponding to the graph is computed.
GC = UndirectedGraphComplex(QQ, implementation='vector', sparse=True)
tetrahedron = GC.cohomology_basis(4, 6)[0]
dGC = DirectedGraphComplex(QQ, implementation='vector')
tetrahedron_oriented = dGC(tetrahedron)

```

```

tetrahedron_oriented_filtered= tetrahedron_oriented.filter(max_out_degree=2)
#tetrahedron_oriented_filtered.show()
tetrahedron_operation= S3.graph_operation(tetrahedron_oriented_filtered)
Q_tetra= tetrahedron_operation(P, P, P, P)
# print('The tetrahedral flow in 3D is', Q_tetra, '\n')

# Now that we have the tetrahedral flow, we see if we can create a vectorfield X
→from our previously computed
# graphs-to-vectorfields such that  $[[P,X]]=Q_{tetra}$ . We first look which
→bivectors  $X_{bivectors}$  the vector fields become
# after taking the Schouten bracket with P.
X_bivectors=[]
for X in X_vector_fields:
    X_bivectors.append(P.bracket(X))

# There are no nonzero (new) vector fields evaluated from 1 graph such that
→ $[[P,X_{graph}]] = 0$ .
zero_bivectors = X_bivectors.count(0)
print('There are', zero_bivectors, 'vector fields in X_vector_fields that
→evaluate to 0 bivectors after taking the Schouten bracket with P .')
print('These vector fields that evaluate to 0 are obtained from the graphs:')
for (k,X) in enumerate(X_bivectors):
    if X==0:
        print('graph', k+1,)
print()

# Now, we extract the monomials appearing in these bivectors (as well as in
→ $Q_{tetra}$ ).
Q_monomial_basis={}
from itertools import combinations
for i,j in combinations(range(2),2):
    Q_monomial_basis[i,j]=set(Q_tetra[i,j].monomials())
    for P_X in X_bivectors:
        Q_monomial_basis[i,j] |= set(P_X[i,j].monomials())

Q_monomial_basis={idx: list(b) for idx, b in Q_monomial_basis.items()}
Q_monomial_index= {idx:{m:k for k,m in enumerate(b)} for idx, b in
→Q_monomial_basis.items()}
Q_monomial_count=sum(len(b) for b in Q_monomial_basis.values());

# We create the vector representation of  $Q_{tetra}$  in terms of the monomials.
Q_tetra_vector= vector(QQ, Q_monomial_count, sparse=True)
index_shift=0
for i,j in Q_monomial_basis:
    for coeff, monomial in Q_tetra[i,j]:
        monomial_index= Q_monomial_index[i,j][monomial]

```

```

        Q_tetra_vector[monomial_index+index_shift]=coeff
        index_shift+=len(Q_monomial_basis[i,j])

# We create the matrix that represents the X_bivectors in terms of the monomials.
X_bivector_evaluation_matrix= matrix(QQ, Q_monomial_count, len(X_bivectors),
    ↪sparse=True)
for k in range(len(X_bivectors)):
    P_X=X_bivectors[k]
    v=vector(QQ,Q_monomial_count, sparse=True)
    index_shift=0
    for i,j in Q_monomial_basis:
        for coeff, monomial in P_X[i,j]:
            monomial_index=Q_monomial_index[i,j][monomial]
            v[monomial_index+index_shift]=coeff
            index_shift+=len(Q_monomial_basis[i,j])
    X_bivector_evaluation_matrix.set_column(k,v)

# We solve the linear system.
X_solution=X_bivector_evaluation_matrix.solve_right(Q_tetra_vector)
print('Proposition 9: The solution on vector fields is given by', X_solution,'
    ↪\n')

# Finally, we will check the homogeneous system. We look at the kernel of the
    ↪X_bivector_evaluation_matrix and filter out the
# nullity of the X_evaluation matrix.
X_cocycle_space= X_bivector_evaluation_matrix.right_kernel().
    ↪quotient(X_evaluation_matrix.right_kernel())
X_cocycles=[X_cocycle_space.lift(v) for v in X_cocycle_space.basis()]
if all(X_bivector_evaluation_matrix*X_cocycle==0 for X_cocycle in X_cocycles)!=
    ↪True:
    print('There is an error in the cocycle space.')
print('The space of solutions to the homogeneous system has dimension',
    ↪X_cocycle_space.dimension(), )
print ('Proposition 10: These shifts are given by', X_cocycles, '\n')

# Let us write the vector fields as vector fields X such that  $[[P,X]]=0$ , rather
    ↪than just the combination of graphs.
shifts_formulas = [sum(X_cocycle[j]*X_vector_fields[j] for j in
    ↪range(len(X_vector_fields))) for X_cocycle in X_cocycles]

# We check that the shifts above is induced by the Hamiltonian vector field.
hamiltonian_encodings= [(1,2,3,0,2,3), (1,2,3,1,2,3), (1,2,3,0,1,3),
    ↪(0,2,3,0,1,3), (0,2,3,1,2,3), (0,1,2,0,1,3), (0,1,2,1,2,3)]

# We create a new encoding to graph definition, as the Hamiltonians are graphs
    ↪on 2 Levi-Civita vertices, 2 Casimir vertices

```

```

# and no sink.
def hamiltonian_encoding_to_graph(encoding):
    targets = [encoding[0:3], encoding[3:6]]
    edges = sum([[ (k+1,v) for v in t ] for (k,t) in enumerate(targets)], [])
    return FormalityGraph(0, 4, edges)
hamiltonian_graphs = [encoding_to_graph(e) for e in hamiltonian_encodings]

# This computation is also slightly different; we do not have the Euler vector
→field since we do not have a sink, and as
# we have only 2 copies of the Poisson bivector, the index_choice for the sign
→is only on 2 repeats as well. Moreover, there
# are only 2 Levi-Civita vertices and 2 Casimir vertices to give vertex_content
→to.
hamiltonian_formulas = []
epsilon = xi[0]*xi[1]*xi[2] # Levi-Civita tensor
for h in hamiltonian_graphs:
    term = S3.zero()
    for index_choice in itertools.product(itertools.permutations(range(3)),
→repeat=2):
        # TODO: Check that this way of evaluating is correct.
        sign = epsilon[index_choice[0]] * epsilon[index_choice[1]]
        vertex_content = [S3(rho), S3(rho), S3(a), S3(a)]
        for ((source, target), index) in zip(h.edges(), sum(map(list,
→index_choice), [])):
            vertex_content[target] = diff(vertex_content[target],
→even_coords[index])
            term += sign * prod(vertex_content)
        hamiltonian_formulas.append(term)

# We create the vector fields [[P,H]] from the Hamiltonians H.
hamiltonian_vector_fields=[]
for hamiltonian in hamiltonian_formulas:
    hamiltonian_vector_fields.append(P.bracket(hamiltonian))

# Create the basis of monomials.
hamiltonian_monomial_basis = {}
for j in range(len(shifts_formulas)):
    for i in range(3):
        hamiltonian_monomial_basis[i] = set(shifts_formulas[j][i].monomials())
        for formula in hamiltonian_vector_fields:
            hamiltonian_monomial_basis[i] |= set(formula[i].monomials())

hamiltonian_monomial_basis = {idx: list(b) for idx, b in
→hamiltonian_monomial_basis.items()}
hamiltonian_monomial_index = {idx: {m : k for k, m in enumerate(b)} for idx, b
→in hamiltonian_monomial_basis.items()}

```

```

hamiltonian_monomial_count = sum(len(b) for b in hamiltonian_monomial_basis.
    ↪values())

# Now, we write the shifts in terms of a vector of the monomials.
def shift_formula_to_vector(shift_formula):
    shift_vector = vector(QQ,hamiltonian_monomial_count, sparse=True)
    index_offset = 0
    for i in hamiltonian_monomial_basis:
        for coeff, monomial in shift_formula[i]:
            monomial_index = hamiltonian_monomial_index[i][monomial]
            shift_vector[monomial_index + index_offset] = coeff
            index_offset += len(hamiltonian_monomial_basis[i])
    return shift_vector

shifts_vectors = [shift_formula_to_vector(shift_formula) for shift_formula in
    ↪shifts_formulas]

# Create the evaluation matrix for the Hamiltonian vector fields.
hamiltonian_evaluation_matrix =
    ↪matrix(QQ,hamiltonian_monomial_count,len(hamiltonian_vector_fields),sparse=True)
for k in range(len(hamiltonian_vector_fields)):
    formula = hamiltonian_vector_fields[k]
    v = vector(QQ, hamiltonian_monomial_count, sparse=True)
    index_shift = 0
    for i in hamiltonian_monomial_basis:
        for coeff, monomial in formula[i]:
            monomial_index = hamiltonian_monomial_index[i][monomial]
            v[monomial_index + index_shift] = coeff
            index_shift += len(hamiltonian_monomial_basis[i])
    hamiltonian_evaluation_matrix.set_column(k, v)

nullity=hamiltonian_evaluation_matrix.right_nullity()
kernel_basis= hamiltonian_evaluation_matrix.right_kernel().basis()
print('The nullity among the Hamiltonian vector fields is ', nullity, '')
# Note that the below is on the level of vector fields, not formulas.
    ↪Unfortunately, the evaluation_matrix procedure only
# works from vector fields onward, and not for 0-vectors (formulas). You can
    ↪explicitly check that the linear relations ARE
# already preserved on the level of formulas by simply evaluating
    ↪hamiltonian_formulas[0]==hamiltonian_formulas[4] etc.
print('Explicitly, these are the linear combinations that evaluate to 0:',
    ↪kernel_basis, '\n')

# We can now solve the shifts! Note that if (at least one) shift is NOT
    ↪Hamiltonian, the code will break here as no solution
# can be found.

```

```

shifts_solutions = [hamiltonian_evaluation_matrix.solve_right(shift_vector) for
↳shift_vector in shifts_vectors]

# Write the solutions above from combinations of graphs to their vector field
↳forms to check validity.
solution_formulas = [sum(shift_solution[i]*hamiltonian_vector_fields[i] for i in
↳range(len(shift_solution))) for shift_solution in shifts_solutions]

if any(P.bracket(solution_formula) != 0 for solution_formula in
↳solution_formulas) or solution_formulas != shifts_formulas:
    print('There is an error in computing the shifts.')
else:
    print('Theorem 12: The shifts in the cocycle space are Hamiltonian.')

for k, shift_solution in enumerate(shifts_solutions):
    print('The shift #', k+1, 'is the following linear combination of
↳Hamiltonian vector fields:', shift_solution)

```

We have 48 graphs.

Lemma 8: There are 41 nonisomorphic graphs.

There are 13 graphs that evaluate to 0 under the morphism from graphs to multivectors.

These graphs are:

graph 12
graph 14
graph 19
graph 27
graph 28
graph 30
graph 35
graph 36
graph 37
graph 38
graph 43
graph 47
graph 48

The vector fields have 28 linear relations among themselves.

There are 13 vector fields in X_vector_fields that evaluate to 0 bivectors after taking the Schouten bracket with P .

These vector fields that evaluate to 0 are obtained from the graphs:

graph 12
graph 14
graph 19

graph 27
graph 28
graph 30
graph 35
graph 36
graph 37
graph 38
graph 43
graph 47
graph 48

Proposition 9: The solution on vector fields is given by $(8, 0, 0, 24, 0, 0, 8,$
 $24, 0, 0, 0, 0, 0, 0, 0, 12, 16, 0, 0, 0, 0, 0, 0, 16, 12, 0, 0, 16, 0, 0, 0,$
 $24, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)$

The space of solutions to the homogeneous system has dimension 3

[illegible]

The nullity among the Hamiltonian vector fields is 3

Explicitly, these are the linear combinations that evaluate to 0: [

$$\begin{bmatrix} (1, 0, 0, 0, -1, 0, 0), \\ (0, 0, 1, 0, 0, 0, 1), \\ (0, 0, 0, 1, 0, 0, -1) \end{bmatrix}$$

Theorem 12: The shifts in the cocycle space are Hamiltonian.

The shift # 1 is the following linear combination of Hamiltonian vector fields:

$$(0, 0, 1, 0, 0, 0, 0)$$

The shift # 2 is the following linear combination of Hamiltonian vector fields:

$$(1/4, 0, 0, 0, 0, 0, 0)$$

The shift # 3 is the following linear combination of Hamiltonian vector fields:

$$(1/2, -1, 0, 0, 0, 0, 0)$$